

EV 57 BLACK

UL LISTED ELECTRICAL TAPE

TYPICAL APPLICATIONS

- Splice, insulate and bind wiring harnesses

ADVANTAGES AND BENEFITS

- High tensile strength and elongation
- Non-corrosive adhesive
- Dielectric at break 1,000 volts/mil

CONSTRUCTION

Overall Grade/Function: UL Listed

Backing: Matte finish, soft polyvinylchloride (SPVC)

Adhesive: Non-corrosive, natural rubber

COLOR(S)



Black (BLK)



STANDARD WIDTH(S)

¾ in 19 mm

STANDARD LENGTH(S)

66 ft 20 m

Contact your Shurtape sales representative for other available sizes.

PHYSICAL PROPERTIES

	STANDARD	METRIC
Tensile Strength	14 lbs/in width	24.5 N/10 mm
Adhesion to Stainless Steel	16 oz/in width	1.75 N/10 mm
Thickness	7.0 mils	0.17 mm
Elongation	200%	200%
Service Temperature Range	20F to 176 F	-7 C to 80 C
Dielectric Strength	1000 volts	1000 volts

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service Departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

APPLICABLE STANDARDS

CID A-A-55809; UL Listed

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.