



P3WSUC WALL-TAP SURGE PROTECTOR

Protect home and office computers, and electronics.

The CyberPower P3WSUC Wall-Tap Surge Protector expands a household outlet to safely and conveniently power several devices from a single location. The wall tap design features swiveling outlets, three AC power outlets with 1500J of surge protection, two USB-A charging ports and 1 USB-C charging port. The P3WSUC provides peace of mind with 1500 joules of surge protection, safeguarding your connected devices and appliances.



TYPICAL APPLICATIONS

- Mobile Devices
- Personal Electronics
- Cell Phones
- Consumer Electronics

FEATURES

- Surge suppression: 1,500 J
- Plug type: NEMA 5-15P
- Outlet type: 3 NEMA 5-15R
- Total USB Output: 18W
- USB-C charge ports: 1
- USB-C charge output: 15W
- USB-A charge ports: 2
- USB charge output: 3.6A (shared)
- Volts: 125 V
- EMI/RFI Filtration: Yes
- Warranty: 1-Year Limited
- Connected Equipment Guarantee: \$100,000

SPECIFICATIONS

INPUT		OUTPUT	
Circuit Breaker	None	Outlet Type	3 NEMA 5-15R
Cord Length	Wall-tap	Outlets - Total	3
Input Plug Type	NEMA 5-15P	USB Charge Port	Yes
Input Voltage	110 - 125 VAC	USB Charge Port Amperage	3.6 Amps (Shared)
Maximum Input Current	15 A	USB Charge Port Quantity	3
Plug Style	Wall-tap	USB Charge Port Type	2 Type A 1 Type C
		USB Charge Port Voltage	5 VDC
		USB Charge Port Watts	15 Watts

P3WSUC

WALL-TAP SURGE PROTECTOR

SPECIFICATIONS - CONT.

SURGE PROTECTION & FILTERING		DIMENSIONS	
Attenuation	32 dB	Physical Dimensions - Width/Height/Depth (cm)	10.31 x 14.76 x 4.72 cm
Clamping Voltage	600V (H-N, H-G, N-G)	Physical Dimensions - Width/Height/Depth (mm)	103 x 148 x 47 mm
EMI/RFI Filtration	Yes	Physical Dimensions - Width/Height/Depth (in.)	4.06 x 5.81 x 1.86 in.
Maximum Surge Current	45,000 A	Weight (kg)	0.26 kg
Maximum Surge Current H-G	15,000 A	Weight (lb)	0.57 lbs.
Maximum Surge Current H-N	15,000 A	SHIPPING DIMENSIONS	
Maximum Surge Current N-G	15,000 A	Shipping Dimensions - Width/Height/Depth (cm)	6.35 x 15.88 x 11.43 cm
Maximum Surge Voltage	6,000 V	Shipping Dimensions - Width/Height/Depth (mm)	63.5 x 158.75 x 114.3 mm
Response Time	<1 Nanosecond	Shipping Dimensions - Width/Height/Depth (in.)	2.5 x 6.25 x 4.5 in.
Surge Suppression (Joules)	1,500 J	Shipping Weight (kg)	0.38 kg
PHYSICAL		Shipping Weight (lbs.)	0.83 lbs.
Color	White	CERTIFICATIONS	
Form Factors Supported	Direct plug	Environmental	RoHS Compliant
Material of Construction	Plastic	Safety	UL498a UL1449 FCC DOE VI
WARRANTY			
CEG Amount	\$100,000	Connected Equipment Guarantee	Lifetime
Product Warranty	1-Year Limited		