

## FROGTAPE® BRAND PAINTER'S TAPE - DELICATE SURFACE

### TYPICAL APPLICATIONS

- For interior use on finished wood, freshly painted walls and trim (24 hours old), coated wallpaper, laminate, vinyl, primed wall board, cabinets and floors

### PRODUCT FEATURES

- Premium grade, delicate surface FrogTape® brand painter's tape
- Low adhesion, solvent-free adhesive system
- Treated with PaintBlock® Technology that seals tape edges for very sharp paint lines
- 60-day clean removal from indoor surfaces
- \*Test before use on all surfaces and when using solvent-based coatings; FrogTape® was designed for use with latex paint; May not be compatible with all floor surfaces - consult floor manufacturer for guidance

### CONSTRUCTION

Backing: Washi paper backing

Adhesive: Synthetic rubber-based adhesive

### STANDARD WIDTHS

0.94 in; 1.41 in; 1.88 in  
24 mm; 36 mm; 48 mm

### STANDARD LENGTH

60.1 yd  
55 m

Lead times may apply. Please contact Shurtape customer service for information related to stock and non-stock sizes and colors.

### STANDARD CORE SIZE

3 in

### APPLICABLE STANDARDS

NA

### STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

### COLOR



### PHYSICAL PROPERTIES

Adhesion to Stainless Steel  
Elongation  
Tensile  
Thickness

### STANDARD

25 oz/in width  
5.0%  
19 lbs/in width  
3.3 mils

### METRIC

2.74 N/10 mm  
5.0%  
33.3 N/10 mm  
0.08 mm

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.



The mark of responsible forestry  
FSC® C154304

\*Test before use on all surfaces and when using solvent-based coatings; FrogTape® was designed for use with latex paint; May not be compatible with all floor surfaces - consult floor manufacturer for guidance