

TOILETS

		WINDHAM™		
		ROUND-FRONT	ELONGATED	COMFORT HEIGHT® ELONGATED
				
1.28 GPF Model Number	12" Rough-In	402320	402321	402322
	14" Rough-In	402367	402368	402369
1.28 GPF Bowl/Tank Model Numbers	12" Rough-In	403017/402362	403217/402362	403317/402362
	14" Rough-In	403017/402365	403217/402365	403317/402365
1.6 GPF Complete Model Number	12" Rough-In	402323	402324	402325
1.6 GPF Bowl/Tank Model Numbers	12" Rough-In	403017/402363	403217/402363	403317/402363
Fill Valve	Fluidmaster 375A			
Trapway	2 1/8" Fully Glazed			
Flushing Technology	Pro Force Plus			
Water Spot	10" x 8"		9 1/2" x 7"	
Trip Lever	Polished Chrome			
Tank-to-Bowl Connection	Factory-Installed Gasket and Three-Bolt Quick-Connect System			
Length x Width x Height	12" Rough-In	27 9/16" x 14 7/8" x 29 1/8"	29 7/16" x 14 7/8" x 28 15/16"	29 3/8" x 14 7/8" x 30 5/16"
	14" Rough-In	29 1/16" x 17" x 28 1/2"	31 1/16" x 17" x 28 1/2"	31 9/16" x 17" x 30"
Bowl Height	15 1/8"		15"	
ADA-Compliant*	No		Yes	

*Products identified as ADA-compliant are compliant when installed per the requirements of the Accessibility Guidelines, Section 604 (Toilets), of the Americans with Disabilities Act.

All combination models conform to the ASME A112.19.2/CSA B45.1 National Consensus Standard.

Note: Toilet seats are not included.

Color Option

White 0

STINSON®	BRELLA®
COMFORT HEIGHT® ELONGATED	COMFORT HEIGHT ELONGATED
	
402396	402095
403316/404558	402101/402098
Fluidmaster 375A	
2" Fully Glazed	
Pro Force Plus	Washdown
9" x 8"	5 1/16" x 4 9/16"
Polished Chrome	
Factory-Installed Gasket and Three-Bolt Quick-Connect System	
29 3/4" x 17 7/16" x 29 3/16"	28" x 18 1/8" x 31 1/4"
16 1/2"	16"
Yes	



To be WaterSense®-labeled, a toilet must meet the following criteria:

- Single-flush toilets must use 1.28 gpf or less
- MaP test or soybean paste test must meet a minimum requirement of 350 grams of waste removed