



Sunny-Side®

super gloss metal interlock floor finish

Extremely high gloss non-buff finish that levels smoothly to highlight floors with the ultimate shine! This metal inter-lock floor finish has mirror like reflective properties to actually double an image for more visual impact! Sunny-Side is tough with strong resistance to black heel marks, scuffing, powdering and water spots.



Providing Quality Maintenance and Chemical Specialty Solutions with Unparalleled Customer Service



Spartan Chemical Company, Inc.
 1110 Spartan Drive
 Maumee, OH 43537
 1-800-537-8990
 www.spartanchemical.com

EASY TO APPLY AND MAINTAIN:

Fundamental application techniques are all that is required for Sunny-Side and basic daily maintenance insures the shine remains brilliant. Sunny-Side will hold its brilliance through numerous detergent moppings and can easily be restored when necessary by spraybuffing. Use on all types of resilient tile floors and terrazzo.

UL APPROVED:

Sunny-Side provides a safe and very glossy surface. Independent testing for slip resistance by Underwriter Laboratories confirms the static coefficient of friction of Sunny-Side, meets or exceeds 0.5 as determined by ASTM Method D 2047.

DIRECTIONS FOR USE:

Some individuals may be sensitive to ingredients in this product. Before using, read product label and MSD sheet. Wet floors may be slippery. Prevent pedestrian traffic with signs or barricades.

INITIAL APPLICATION:

Strip: Completely strip all old wax or floor finish. Depending upon build-up, use warm or room temperature water (80° - 120°F) and a Spartan stripper.

Seal: Apply two coats of a Spartan seal. Let dry.

Finish: Apply three uniform coats of Sunny-Side. Let each coat dry 30 minutes or until surface is completely dry to the touch. Apply subsequent coats in the same manner. Gloss and depth dramatically improve with more coats. Subsequent coats should be applied over a period of time.

MAINTENANCE:

Daily: Dust mop with Dust Mop Treatment and damp mop with a neutral Spartan cleaner.

Periodically: Dust mop with Dust Mop Treatment and damp mop with a neutral Spartan cleaner. To repair traffic areas between finish applications, use Spartan Bounce Back, Spraybuff or SunSwept.

As Needed: Deep scrub and recoat; or completely strip, reseal and reapply floor finish.

NOTE: For best maintenance results always use Spartan floor cleaners and strippers.

Be sure to read all Directions, Precautionary and First Aid Statements on product labels before use of this or any Spartan product. If questions remain, consult your employer or a physician. Material Safety Data Sheets for all Spartan products are available from your authorized Spartan distributor or by visiting

www.spartanchemical.com.

SPECIFICATIONS:

Total Solids – 23.3%
 Non-Volatile Solids – 18%
 Specific Gravity – 1.028 @24°C/75°F
 pH (Concentrate) – 8.7 - 9.1

Stability

- a. Storage – One year
- b. Accelerated @ 49°C / 120°F – 30 days minimum
- c. Freeze / Thaw – Can withstand three cycles

Gloss (Gardner)

- a. 1 coat – 75-80
- b. 2 coats – 85-90

Static coefficient of friction meets or exceeds 0.5 as determined by ASTM method D-2047.

COVERAGE:

Up to 3,000 square feet per gallon depending on application method and porosity of floor.



Distributed by:

PACKAGING	
404565	330-gallon totes
404555	55-gallon drum
404530	30-gallon drum
404515	15-gallon drum
404505	5-gallon pail
404504	1-gallon (4 per case)



Label copy is available in English, Spanish and French. Secondary labels are also available.

GUARANTEE: Spartan's modern manufacturing and laboratory control insure uniform quality. If dissatisfied with performance of product, any unused portion may be returned for credit within one year of the date of manufacture. Use product as directed and read all precautionary statements.



Product Available Worldwide. For institutional and industrial use only.

© SCC 5/11 L4045