

**SCP PART#: 22/10-500**

01/21

Description : 10C/22 AWG 7 Strand BC Multipurpose Security/Alarm Cable, UL CMR, PVC Jkt  
 White - 500 FT Spool

Conductor : 22 AWG 7x.0097 Bare Copper	
Total Cable Weight : 49 kg/km	Final Diameter : 0.195 inches / 4.95mm
Insulation : PVC	Jacket : PVC
DC Resistance 25°C: 18.4 Ohms / 500ft	Mutual Capacitance : 41.9 pF/ft
Impedance : 54.9 Ohms	Cond to Shield Cap. : 67.9 pF/ft
Velocity of Prop : 60 %	Inductance. : 1.3 mH/km

Print Notes : Sequentially marked per 2FT (0 - infinity)

Standard Print : STRUCTURED CABLE PRODUCTS - - - P/N 22/10 - - - (UL) CL3R E198137  
 (UL) C(UL) CMR UNSH 10/C 22 AWG - - - ZONE/DEVICE A B C D E 0 1 2  
 3 4 5 6 7 8 9 RoHS

Cabled OD Avg: 0.133	NEC Articles: 800, 725
Ins Thickness: 0.006	Min. Bend Radius/Minor Axis: 1.155 inches
Jkt Thickness: 0.015	Operating Temperature : -20°C to 60°C
Certified: UL CL3R/CMR	Standard UL Temp : 60°C
Flame Rating: Riser	
Max Voltage: 300V	

Package Weight: 19.50 lbs / 8.86 kgs

( All of the above values are approximated to within +/- 10% )