CRC CO Contact Cleaner

I. Product Description

CRC CO Contact Cleaner is a plastic-safe general-purpose evaporating cleaner and degreaser for use on sensitive electronic and electrical equipment. It is formulated to quickly penetrate into hard-to-reach areas and effectively flush away carbon deposits, dirt, light oils, dust, lint and other light contaminants.

CRC CO Contact Cleaner as part of a regular maintenance programme will eliminate carbon deposits and other contaminants that hold moisture and cause corrosion or arcing. An increase in resistance will indicate the frequency of re-application.

Use on de-energised equipment only.

II. Features & Benefits

- Safe for use on most plastics
- Quickly penetrates into hard-to-reach areas
- Rapid and complete evaporation Leaves no residue, no rinsing or wiping required
- Low in toxicity
- High purity formula
- Chemically stable, inert
- Non-conductive, non-corrosive, non-staining
- Contains no lubricants, silicones, oils
- MPI Approved C12
- USDA Authorised for use in Federally inspected Meat and Poultry Plants
- NSN 6850-98-104 5702
- Includes Permastraw[™] Dual-Action Spray System One piece actuator with two-way spray that ensures that straw stays in place.

III. Directions for Use

- De-activate equipment before use.
- Test on plastic substrates before use.
- Apply by spraying onto surface.
- Use extension tube for hard-to-reach areas.
- For oxidation or corrosion on contact surfaces, use an abrasive or burnish. Remove cleaning residue with CRC CO Contact Cleaner before re-activating equipment.
- Ventilate after use.

IV. Typical Properties and Characteristics

Physical Properties:

| Propellant (Aerosol) | Carbon Dioxide |
|----------------------|----------------|
| Flash Point | <0°C |
| Appearance | Clear liquid |
| Odour | Mild |
| Boiling Point | 60.5°C |
| Specific Gravity | 0.67 |
| Surface Tension | 21 Dynes/cm |
| % Volatiles | 100 |
| Flammability | Flammable |



CRC CO Contact Cleaner

Performance Characteristics:

| Dielectric Strength | 40,000 Volts per ASTM D-877 |
|---------------------|-----------------------------|
| KB Value | 31 |

V. Package Description

| T dit Hamber | CIEC |
|--------------|--|
| 2015 | 210ml Aerosol + Permastraw™ Dual-Action Spray System |
| 2016 | 500ml Aerosol + Permastraw™ Dual-Action Spray System |

Siza

VI. Special Precautions

General:

Part Number

Extremely flammable aerosol. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Avoid breathing dust/fume/gas/mist/vapours/spray. Use only outdoors or in a well-ventilated area. Use personal protective equipment as required. Store in a well-ventilated place. Keep container tightly closed. Store locked up. Dispose of empty containers safely. All unused product should be disposed of in conformance with local and HSNO regulations, do not contaminate water supply.

Aerosol Cans:

Do not puncture, incinerate or store above 50°C. Exposure to high temperatures may cause can to burst. Do not place in direct sunlight or near any heat source. Aerosol cans will conduct electricity. Keep away from all live electrical sources including battery terminals, solenoids, electrical panels and other electronic components. Failure to observe this warning may result in serious injury from flash fire and/or electrical shock.

First Aid:

Swallowed – Not considered a normal route of entry. Avoid giving milk or oils. Avoid giving alcohol.

Skin – Flush skin and hair with running water (and soap if available). Remove any adhering solids with industrial skin cleansing cream. DO NOT use solvents. Seek medical attention in the event of irritation.

Eyes – Immediately hold the eyelids apart and flush the eye continuously for at least 15 minutes with fresh running water. Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. Transport to hospital or doctor without delay.

Inhalation – Remove to fresh air. Lay patient down. Keep warm and rested.

Refer to Material Safety Data Sheet for more details.

TECHNICAL DATA SHEET Version 08/2015

PRODUCT WARRANTY: CRC offers a conditional warranty of this product for the period of 2 years from the date of manufacture.

DISCLAIMER: All information on this data sheet is based on testing by CRC Industries NZ. All products should be tested for suitability on a particular application prior to actual use. CRC Industries makes no representations or warranties of any kind concerning this data.