

2024 Specification Sheet - English



LONG DESCRIPTION –

Long Description Marketing Copy

SPEED PUNCH® saves time and money with every hole.. Up to 3X's faster setup and disassembly.. No-Thread punch design eliminates cross-threading.. Available in 3/4" - 2" conduit sizes and punch kits

PRODUCT NAME –

Page Title

Speed Punch® Draw Stud 3/4" x 5.64"

PRODUCT OVERVIEW –

Marketing Text 1

SPEED PUNCH® saves time and money with every hole.

Marketing Text 2

Up to 3X's faster setup and disassembly.

Marketing Text 3

No-Thread punch design eliminates cross-threading.

Marketing Text 4

Available in 3/4" - 2" conduit sizes and punch kits

PRODUCT SPECIFICATION –

Product Specification 1

Application : For punching conduit sized holes in mild steel, aluminum, fiberglass, and plastic.

Product Specification 2

Capacity : Mild steel up through 10 gauge (3.5 mm).

Product Specification 3

Driver : Use with Greenlee Hydraulic Ram (746).

Product Specification 4

Material : Carbon Steel, Black Oxide Coated

Product Specification 5

Operation : Must be used with other SPEED PUNCH® System components.

Product Specification 6

Size : 3/4" x 5.63"

Product Specification 7

Sub Brand : SPEED PUNCH®

Product Specification 8

Type : Knockout Punches

Product Specification 9

Weight : 0.65 lbs. (0.30 kg)