# Assault® Floor Stripper HIL0014907





Strips away extreme build-ups of water emulsion waxes and polishes without repeated scrubbing. Removes polish coats that have been repeatedly burnished and hardened with ultra high-speed floor machines. Ideal for stripping floors in hard-to-reach areas. Removes heavy build- ups, even in cold water, with or without machine scrubbing. Butyl-free, low odor formula solves the toughest stripping problems on quarry tile, paver brick, terrazzo, concrete and vinyl composition flooring. Do not use on asphalt, linoleum, rubber or painted surfaces. Low odor formula.

#### **Features & Benefits**

**Butyl-free** 

Low odor lessens impact on building occupants

Concentrated for economical cost-in-use

Use with cold water with or without a scrubbing machine

### **Item Number & Unit of Measure**

Item Number	HIL0014907
Unit of Measure	5 gal BIB

### **Specifications**

Color	Light Amber
-------	-------------

Appearance	Clear
Fragrance	Mild Solvent
Formula Type	Liquid
Dilution Ratio	1:5 - 1:1
PH	12.00 - 13.00
Non-Volatile Matter	4.50 - 5.50%

## **Safety**

See safety datasheet (if applicable) and product label for safety information, handling and proper use.

### **Directions for Use**

Do not use on asphalt tile, linoleum, rubber, painted, or varnished surfaces. DO NOT USE ON WOOD. (Do not use abrasive pads on tile containing asbestos.)PRETEST: Test on an inconspicuous area using 1:1 dilution. Allow to stand on the floor 10 minutes. Wipe off with towel, rinse, and examine floor for bleeding or softening. Do not continue use of product if any is observed. APPLICATION: Do not use with hot water or spray method. Apply with clean mop to a small area (less than 200 sq. ft.) at 1:3 dilution (may be increased to 1:2 or 1:1 for heavy buildup). Allow to stand 3 to 5 minutes, then agitate with mop. Do not allow solution to dry on floor. Assault may be used with a floor machine for extremely heavy buildup (dilute 1:5 with water). Use the least abrasive pad possible for stripping. NOTICE: Floor may become slippery when stripper is present. Pick up solution immediately with wet vac or mop. Damp mop rinse. Apply polish after floor is clean and dry. Stripper vapors or liquid may cause discoloration on uncured, light colored painted surfaces. DO NOT USE ON GLASS.