

ACCESS CONTROL



SURFACE MOUNT AND RECESSED DOOR AND WINDOW CONTACTS DOOR AND WINDOW CONTACTS

	MODEL	CONTACT SIZE	MAGNET SIZE	PKG QUANTITY	FEATURES	LEAD WIRE
	FM-102 Surface Mount	1.32" x 0.3" x 0.53" (3.3 x 0.7 x 1.3 cm)	1.32" x 0.3" x 0.53" (3.3 x 0.7 x 1.3 cm)	10	Flange Mount & Adhesive	12" (30.5cm) 22 AWG Leads Standard
	FM-106 Flange Mount Self Stick	1.32" x 0.3" x 0.51" (3.3 x 0.7 x 1.3 cm)	1.32" x 0.3" x 0.51" (3.3 x 0.7 x 1.3 cm)	10	Side Lead Option	12" (30.5cm) 22 AWG Leads Standard
	MET-200AR Commercial Contact	2" x 0.74" x 0.37" (5.1 x 1.9 x 0.9 cm)	2" x 0.74" x 0.37" (5.1 x 1.9 x 0.9 cm)	1	Available with 18" (45.72 cm) & 36" (91.44 cm)Armoured Cables	18" (45.8cm) Armor Cable Standard (MET-200AR)
	MET-44WG-18 Metal Cased Overhead Door Contact	1.73" x 4.22" x 0.47" (4.4 x 10.7 x 1.2cm)	2.42" x 4.13" x 1.50" (6.8 x 10.5 x 3.8cm)	1	Available with 18" (45.72 cm) and 36" (91.44 cm) Armored Cable	18" (45.8cm) Armored Leads
	TANE-MICRO Ultra Thin Surface Mount	0.31" x 0.67" x 0.16" (0.8 x 1.7 x .4cm)	0.31" x 0.67" x 0.16" (0.8 x 1.7 x .4cm)	10	Smaller than a dime	12" (30.5cm) 22 AWG Leads Standard
	SM-35 Commercial Contact	0.48" x 2.48" x 0.51" (1.2 x 6.3 x 1.3 cm)	0.48" x 2.48" x 0.51" (1.2 x 6.3 x 1.3 cm)	10	Free Spacers Screws, Cover	N/A
	RB-32 Commercial Contact	1.89" x 0.72" (4.8 x 1.8 cm)	N/A	10	Free Spacers Screws, Cover	12" (30.5cm) 22 AWG Leads Standard
	MINI10 3/8" Mini Recess	0.61" x 0.37" (1.6 x 1 cm)	0.61" x 0.37" (1.55 x .95 cm)	10	Tight Fit Magnet	12" (30.5cm) 22 AWG Leads Standard
	TANE-45 Mini Surface Mount	0.27" x 1.06" x 0.19" (0.7 x 2.7 x .5 cm)	0.27" x 1.06" x 0.19" (0.7 x 2.7 x .5 cm)	10	Ideal for Tight Fit Windows	12" (30.5cm) 22 AWG Leads Standard
	STB-3/8TC 3/8" Quick Connect	0.92" x 0.37" (2.4 x 1.0 cm)	0.61" x 0.37" (1.6 x 1.0 cm)	10	Quick Connect (Terminals)	STB-3/8 TC: Terminal Connect, No Leads
	TANE-3/4TC 3/4" Quick Connect	1.18" x 0.75" (3.0 x 1.9 cm)	0.85" x 0.76" (2.2 x 1.9 cm)	10	Steel Door Type	Terminal Connect, No Leads

1

ACCESS CONTROL



ACCESS CONTROL

SURFACE MOUNT AND RECESSED DOOR AND WINDOW CONTACTS *DOOR AND WINDOW CONTACTS*

1

ACCESS CONTROL

SPECIFICATIONS

Part Number	Gap Inch (cm)	Security Loop Open/Closed (Magnet Present)	Reed Form (Magnet Removed)	Max. Con- tact Rating (W)	Max. Initial Contact Resistance	Max. Switching Voltage (V)	Max. Switching Current (A)
FM-102	0.83" (2.1)	CLOSED	Normally Open	10	100	AC110/DC100	0.5
FM-106	0.83" (2.1)	CLOSED	Normally Open	10	100	AC110/DC100	0.5
MET-200AR	1.25" (3.2)	CLOSED	Normally Open	10	100	AC110/DC100	0.5
MET-44 WG	2" (5.0)	CLOSED	Normally Open	10	100	AC110/DC100	0.5
TANE MICRO	0.32" (.8)	CLOSED	Normally Open	1	100	AC24/DC24	0.1
SM-35	0.91" (2.3)	CLOSED	Normally Open	10	100	AC110/DC100	0.5
RB-32	NA	CLOSED	Normally Open	10	100	AC110/DC100	0.5
MINI-10	0.5" (1.25)	CLOSED	Normally Open	10	100	AC24/DC24	0.1
TANE-45	0.44" (1.1)	CLOSED	Normally Open	1	100	AC24/DC24	0.1
STB-3.8 TC	0.6" (1.5)	CLOSED	Normally Open	10	100	AC110/DC100	0.5
TANE-3/4 TC	1.1" (2.8)	CLOSED	Normally Open	10	100	AC110/DC100	0.5