



P403URC1 | HOME OFFICE SURGE PROTECTION

Protect home and office computers, electronics, and home theater equipment

The CyberPower Home Office Surge Protector P403URC1 prevents spikes in energy caused by storms and electrical power surges from reaching your home office equipment such as laptops, small electronics, and chargers. The P403URC1 provides 500 joules of protection, 4 AC outlets, and a 3-ft. power cord with a right-angle plug. It also has 2 USB ports (2.4 Amp) to quickly charge USB-powered devices.

Features of the P403URC1 include automatic shutdown, an EMI/RFI noise filter, metal oxide varistor (MOV) technology, an On/Off switch with integrated 15-Amp circuit breaker, LED indicator, low profile cord plug, keyhole mounting slots, and damage-resistant construction. This surge suppressor comes with a 1-Year Limited Warranty and a \$15,000 Connected Equipment Guarantee.

TYPICAL APPLICATIONS

- Mobile Devices
- Personal Electronics
- Cell Phones
- Consumer Electronics

FEATURES

- Surge suppression: 500 J
- Volts: 125 V
- Circuit breaker: 15 A
- USB ports: (2) 2.4-Amp
- Outlets: 4 surge-protected (standard)
- Plug style: Right-angle 45° offset
- Power cord: 3 ft
- Color: White
- EMI/RFI Filtration: Yes
- Connected Equipment Guarantee: \$15,000
- Warranty: 1-Year Limited



SPECIFICATIONS

INPUT	
Circuit Breaker	15 A
Cord Length	3 ft (0.9 m)
Input Plug Type	NEMA 5-15P
Maximum Input Current	15 A
Plug Style	Right Angle - 45° Offset

OUTPUT	
Outlet Type	4 NEMA 5-15R
Outlets - Total	4
USB Charge Port	Yes
USB Charge Port Amperage	2.4 Amps (Shared)
USB Charge Port Quantity	2
USB Charge Port Type	Type A
USB Charge Port Voltage	5 VDC

P403URC1

HOME OFFICE SURGE PROTECTION

SPECIFICATIONS CONT.

SURGE PROTECTION & FILTERING	
Attenuation	32 dB
Clamping Voltage	800V (H-N)
EMI/RFI Filtration	150 KHz 100 MHz Yes
Maximum Surge Current	15,000 A
Maximum Surge Current H-G	N/A
Maximum Surge Current H-N	15,000 A
Maximum Surge Current L-N	15,000 A
Maximum Surge Current N-G	N/A
Maximum Surge Voltage	6,000 V
Response Time	<1 Nanosecond
Surge Suppression (Joules)	500 J
PHYSICAL	
Color	White
Form Factors Supported	Keyhole (Wall Mount or Under-counter Installation)
Keyhole Mounting Slots	Yes
Material of Construction	Plastic

DIMENSIONS	
Physical Dimensions - Width/Height/Depth (cm)	4.72 x 3.45 x 24.99 cm
Physical Dimensions - Width/Height/Depth (mm)	47 x 35 x 250 mm
Physical Dimensions - Width/Height/Depth (in.)	1.86 x 1.36 x 9.84 in.
Weight (kg)	0.33 kg
Weight (lb)	0.72 lbs.

SHIPPING DIMENSIONS	
Shipping Dimensions - Width/Height/Depth (cm)	9.3 x 29.31 x 3.56 cm
Shipping Dimensions - Width/Height/Depth (mm)	92.96 x 293.12 x 35.56 mm
Shipping Dimensions - Width/Height/Depth (in.)	3.66 x 11.54 x 1.4 in.
Shipping Weight (kg)	0.45 kg
Shipping Weight (lbs.)	1.00 lbs.

CERTIFICATIONS	
Environmental	RoHS Compliant
Safety	UL1449 3rd Edition cUL

WARRANTY	
CEG Amount	\$15,000
Connected Equipment Guarantee	Lifetime
Product Warranty	1-Year Limited