

CyberPower

CP1350AVRLCD INTELLIGENT LCD UPS SYSTEM

Offers significant energy savings, battery backup and surge protection.

A mini-tower UPS with line interactive topology, the CyberPower Intelligent LCD CP1350AVRLCD provides battery backup (using simulated sine wave output) and surge protection for desktop computers, workstations, networking devices, and home entertainment systems. The CP1350AVRLCD uses Automatic Voltage Regulation (AVR) to correct minor power fluctuations without switching to battery power, which extends battery life. AVR is essential in areas where power fluctuations occur frequently. The CP1350AVRLCD comes with a three-year warranty (including coverage of batteries) and a \$500,000 Connected Equipment Guarantee.

TYPICAL APPLICATIONS

- Desktop Computers
- Automatic Voltage Regulation
- Workstations
- Home Theater Equipment
- Personal Electronics
- Home Networking
- Routers & Modems
- VoIP Phone Systems

FEATURES

- Capacity: 1350 VA / 815 W
- Topology: Line Interactive
- Waveform: Simulated Sine Wave
- Output: 120 VAC +/- 5%
- Runtime (half/full): 14 minutes / 4 minutes
- Plug type & cord: NEMA 5-15P, 6 ft. cord
- Outlets: 10 (5 surge, 5 surge + battery backup)
- Outlet types: NEMA 5-15R
- Communication: USB, Serial
- Data line protection: Ethernet, Coaxial
- Management software: PowerPanel® Personal
- Warranty: Three-Year
- Connected Equipment Guarantee: \$500,000
- ENERGY STAR® certified: Yes



CP1350AVRLCD

INTELLIGENT LCD UPS SYSTEM

SPECIFICATIONS

GENERAL

Energy Saving	GreenPower UPS™ Bypass Technology
ENERGY STAR® certified	Yes
UPS Topology	Line Interactive

INPUT

Circuit Breaker	15 A
Cord Length	6 ft (1.8 m)
Input Frequency Range	57 Hz - 63 Hz
Input Plug Type	NEMA 5-15P
Input Voltage Range	90 VAC - 142 VAC
Nominal Input Voltage	120 VAC
Plug Style	Right Angle - 45° Offset

OUTPUT

Automatic Voltage Regulation	Single Boost
On Battery Frequency	60 Hz +/- 1%
On Battery Voltage	120 VAC +/- 5%
On Battery Waveform	Simulated Sine Wave
Outlet Type	10 x NEMA 5-15R
Outlets - Battery & Surge Protected	5
Outlets - Surge-Only Protected	5
Outlets - Total	10
Output Power Factor	0.6
Overload Protection	Internal Circuitry Limiting Circuit Breaker Protected
Typical Transfer Time	4 ms
Under/Over-Voltage Correction	+10%
VA	1350 VA
Watts	815 W

BATTERY

Battery Capacity	9 Ah
Battery Quantity	2
Battery Size	12 Volts / 9 Ah
Battery Type	Sealed Lead-Acid Battery
Battery Voltage	12 VDC
Hot-Swappable	Yes



BATTERY - CONT.

Replacement Battery Cartridge	RB1290X2 (for serial numbers that begin with "CTJ" or "CDN") RB1280X2A (for serial numbers that begin with "CPK")
Replacement Battery Cartridge	1
Runtime at Full Load	4 min
Runtime at Half Load	14 min
Typical Recharge Time	8 Hours
User-Replaceable Battery	Yes

SURGE PROTECTION & FILTERING

Coaxial Protection RG6	1 in / 1 out
EMI/RFI Filtration	Yes
Network Protection RJ45	1-in / 1-Out (10/100/1000)
Phone / Network Protection RJ11/RJ45	1-In / 1-Out (Combo)
Surge Suppression	1500 J

CP1350AVRLCD

INTELLIGENT LCD UPS SYSTEM

SPECIFICATIONS - CONT.

MANAGEMENT & COMMUNICATIONS		SHIPPING DIMENSIONS	
Audible Alarms	Battery Mode Low Battery Overload Fault	Shipping Dimensions - Width/Height/Depth	20.02 x 34.62 x 46.05 cm
HID Compliant USB Port	Yes	Shipping Dimensions - Width/Height/Depth	200.15 x 346.2 x 460.5 mm
LCD	Multifunction LCD	Shipping Dimensions - Width/Height/Depth	7.88 x 13.63 x 18.13 in.
LCD Backlight	Black	Shipping Weight (kg)	8.22 kg
LED Indicators	Power On Wiring Fault	Shipping Weight (lbs.)	18.13 lbs.
Management Cable	USB Cable	ENVIRONMENTAL	
Serial Port	1 Dry Contact	Operating Elevation	0 - 10,000 ft (0 - 3,048 m)
Software (Free Download)	PowerPanel® Personal	Operating Relative Humidity	0 - 90% (non-condensing)
PHYSICAL		Operating Temperature	32 - 104 °F (0 - 40 °C)
Color	Black	Storage Elevation	0 - 50,000 ft (0 - 15,239 m)
Form Factor	Mini-Tower	Storage Relative Humidity	0 - 95% (non-condensing)
Material of Construction	Plastic	Storage Temperature	5 - 113 °F (-15 - 45 °C)
PHYSICAL DIMENSIONS		CERTIFICATIONS	
Physical Dimensions - Width/Height/Depth (cm)	9.91 x 24.89 x 34.8 cm	Environmental	RoHS Compliant
Physical Dimensions - Width/Height/Depth (mm)	99 x 249 x 348 mm	Safety	UL1778 cUL 107 5th FCC DOC Class B
Physical Dimensions - Width/Height/Depth (in.)	3.9 x 9.5 x 13.7 in.	WARRANTY	
Weight (kg)	10.16 kg	Connected Equipment Guarantee (CEG)	Lifetime
Weight (lbs.)	22.4 lbs.	CEG Amount	\$500,000
		Extended Warranty Option	WEXT5YR-U2A
		Product Warranty	3-Year Limited