



MP60BK MULTI PACK SOLUTIONS

Save your devices and money with a three-pack of surge protectors

The Cyberpower Surge Protector MP60BK combo pack comes with two three-outlet surge protector strips, and one two-outlet wall-tap surge protector. Each surge protector in this combo pack provides protection to prevent damaging power spikes and surges from reaching your small electronics. These surge protectors include USB ports to quickly charge USB-powered devices, including tablets.

Additional features of the MP60BK combo pack include metal oxide varistor (MOV) technology, a Power ON LED indicator (wall-tap only), a braided power cord (strips only), and impact-resistant casing. All three surge protectors come with a 1-Year Limited Warranty and a \$50,000 Connected Equipment Guarantee.

TYPICAL APPLICATIONS

- Personal Computers
- Chargers
- Personal Electronics



FEATURES

SURGE PROTECTOR POWER STRIPS

- Surge suppression: 350 J
- USB ports: 2 (2.4 Amp)
- Plug type: NEMA 5-15P (45° offset)
- Outlet type: 3 NEMA 5-15R
- Power cord length: 3 ft.
- Power cord type: braided
- Warranty: 1-Year Limited
- Connected Equipment Guarantee: \$50,000

SURGE PROTECTOR WALL-TAP

- Surge suppression: 600 J
- Volts: 125 V
- Plug type: 3 Prong Direct Plug-in
- Outlet type: 2 NEMA 5-15R
- USB charge ports: 3 (4.2-Amp)
- Warranty: 1-Year Limited
- Connected Equipment Guarantee: \$50,000

SPECIFICATIONS

INPUT	SURGE STRIP	WALL-TAP
Cord Length	3 ft (0.9 m)	N/A
Plug Type	NEMA 5-15P	
Maximum Input Current	15A	
Plug Style	45° Offset	Wall-tap
OUTPUT		
Outlet Type	NEMA 5-15R	
Outlets - Total	3	2
USB Charge Ports	2	3
USB Charge Ports Amperage	2.4 A	4.2 A

OUTPUT - CONT.	SURGE STRIP	WALL-TAP
USB Charge Port Type	Type A	Type A
USB Charge Port Voltage	5 VDC	5 VDC
SURGE PROTECTION & FILTERING		
Clamping Voltage	900 V	800 V
Maximum Surge Current H-N	7,500 A	15,000 A
Maximum Surge Voltage	6,000 V	
Response Time	< 1 nanosecond	
Surge Suppression	350J	600J

MP60BK

MULTI PACK SOLUTIONS

SPECIFICATIONS CONT.

PHYSICAL	
Color	Black
Material of Construction	Plastic
SHIPPING DIMENSIONS	
Shipping Dimensions - WxHxD (cm)	16.51 x 21.92 x 9.86 cm
Shipping Dimensions - WxHxD (mm)	165.1 x 219.2 x 98.55 mm
Shipping Dimensions - WxHxD (in)	6.5 x 8.63 x 3.88 in.
Shipping Weight (kg)	0.76 kg
Shipping Weight (lbs.)	1.68 lbs.

CERTIFICATIONS	
Environmental	RoHS Compliant
Safety	UL498A UL1310 UL817 UL1449 FCC DOE VI TUV
WARRANTY	
CEG Amount	\$50,000
Connected Equipment Guarantee	Lifetime
Product Warranty	1-Year Limited