



Technical Data Sheet

3M™ Thermoset Heat Activated Film 7110B



[Regulatory Info/SDS](#)

Product Description

3M™ Thermoset Heat Activated Film(HAF) 7110B adhesive is a 100 micron tacky film that is laminated at room temperature. It is then cured at low temperature to form a high strength bond.

Product Features

- Adjustable trigger cure starting at 65°C
- Room temperature tack
- Excellent drop performance
- 100% Solids
- Halogen compliant

Technical Information Note

The following technical information and data should be considered representative or typical only and should not be used for specification purposes.

Typical Uncured Physical Properties

Attribute Name	Value
Base Resin	Proprietary

Typical Physical Properties

Attribute Name	Test Method	Value
Color		Black
Liner		PET release liner
Liner Thickness		0.075 mm
Total Thickness with liner		0.25 mm
Total Tape Thickness	ASTM D3652	0.1 mm

Typical Cured Characteristics

Attribute Name	Test Method	Value
Young's Modulus		170 MPa ¹
Elongation	ASTM D638	230 % ²

¹ Tested in accordance with ASTM D638 test method, Type IV dogbone. Jaw separation 100mm/min. Sample removed from a dry condition and tested after equilibration at 25°C / 50%RH within 2 hours.

² Type IV dogbone. Jaw separation 100mm/min. Sample removed from a dry condition and tested after equilibration at 25°C / 50%RH within 2 hours.

Typical Performance Characteristics

Attribute Name	Test Method	Dwell Time	Temperature	Substrate	Value
180° Peel Adhesion	ASTM D3330	1 h	80 °C (175 °F)	Etched Aluminum	1.7 N/mm
Liner Release			22 °C (72 °F)		Tight Side: 10-40. Easy Side 4-10. g/in

Attribute Name	Test Method	Dwell Time	Temperature	Substrate	Value
Tensile Strength					36 MPa ¹

¹ Tested in accordance with ASTM D638 test method, Type IV dogbone. Jaw separation 100mm/min. Sample removed from a dry condition and tested after equilibration at 25°C / 50%RH within 2 hours.

Overlap Shear Strength

Temperature: 22 °C (72 °F)

Test Method: ASTM D1002, ISO 4587

Substrate	Value
Etched Aluminum	16.2 MPa ¹
Stainless Steel	6.5 MPa ¹
Polycarbonate (PC)	5.6 MPa ¹
GFPC	6 MPa ¹
ABS	5.1 MPa ¹

¹ Cured in an 80 °C oven for 1 hour

Electrical and Thermal Properties

Test Condition: Mid-Point

Attribute Name	Value
Glass Transition Temperature (Tg)	26 °C ¹

¹ Glass Transition Temperature (Tg) determined using DSC Analyzer with a heating rate of 68°F (20°C) per minute. Second heat values given.

Handling/Application Information

Surface Preparation

A clean bonding surface is essential for maximum performance. For metals, chemical etching results in ultimate adhesion. Abrading the metal bonding surface with a 3M™ Scotch-Brite™ Abrasive Pad, and cleaning with MEK will improve bond strength. For plastic bonding cleaning the surface is recommended to remove oils, mold release agents, and solid contaminants prior to bonding. Surface roughness (VDI) finish on plastic of 27 to 33 also improves bond strength. For preparing other substrates for bonding contact your 3M application or technical service engineer.

Storage and Shelf Life

The shelf life of 3M™ Thermoset HAF 7110B is 12 months from the date of manufacture when stored in the original packaging materials at 4°C (25°F). Store die cut parts at the same temperature (4°C, 25°F) in a sealed bag prior to use or shipping. During use, material is stable for up to 4 weeks at room temperature (25°C).

Automotive Disclaimer

Select Automotive Applications:

This product is an industrial product and has not been designed or tested for use in certain automotive applications, such as automotive electric powertrain battery or high voltage applications, which may require the product to be manufactured in a IATF certified facility, meet a Ppk of 1.33 for all properties, undergo an automotive production part approval process (PPAP), or fully adhere to automotive design or quality system requirements (e.g., IATF 16949 or VDA 6.3). Customer assumes all responsibility and risk if customer chooses to use this product in these applications.

Information

Technical Information: The technical information, guidance, and other statements contained in this document or otherwise provided by 3M are based upon records, tests, or experience that 3M believes to be reliable, but the accuracy, completeness, and representative nature of such information is not guaranteed. Such information is intended for people with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. No license under any 3M or third party intellectual property rights is granted or implied with this information.

Product Selection and Use: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application, including conducting a workplace hazard assessment and reviewing all applicable regulations and standards (e.g., OSHA, ANSI, etc.). Failure to properly evaluate, select, and use a 3M product and appropriate safety products, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property.

Warranty, Limited Remedy, and Disclaimer: Unless a different warranty is specifically stated on the applicable 3M product packaging or product literature (in which case such warranty governs), 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR

CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. If a 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability: Except for the limited remedy stated above, and except to the extent prohibited by law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.

Disclaimer: 3M industrial and occupational products are intended, labeled, and packaged for sale to trained industrial and occupational customers for workplace use. Unless specifically stated otherwise on the applicable product packaging or literature, these products are not intended, labeled, or packaged for sale to or use by consumers (e.g., for home, personal, primary or secondary school, recreational/sporting, or other uses not described in the applicable product packaging or literature), and must be selected and used in compliance with applicable health and safety regulations and standards (e.g., U.S. OSHA, ANSI), as well as all product literature, user instructions, warnings, and limitations, and the user must take any action required under any recall, field action or other product use notice. Misuse of 3M industrial and occupational products may result in injury, sickness, or death. For help with product selection and use, consult your on-site safety professional, industrial hygienist, or other subject matter expert. For additional product information, visit www.3M.com.

3M™ Electronics Materials Solutions Division
3M Center, St. Paul, MN 55144-1000
3M.com/electronics