



P6WSUC WALL-TAP SURGE PROTECTION

Protect home and office computers, and electronics.

The CyberPower Wall-Tap Surge Protector P6WSUC prevents spikes in energy caused by storms and electrical power surges from reaching your home electronics. The P6WSUC provides 1500 joules of protection and six AC outlets with a single wall tap plug. The USB-C and USB-A ports charge USB powered devices.

Features of the P6WSUC include rotatable outlets, automatic shutdown, an EMI/RFI noise filter, metal oxide varistor (MOV) technology, and a surge protection LED indicator. This surge suppressor comes with a One-Year Limited Lifetime Warranty and a 100,000 Connected Equipment Guarantee.



TYPICAL APPLICATIONS

- Consumer Electronics
- Personal Computers
- Chargers
- Home Theater Equipment
- Network Devices

FEATURES

- Surge suppression: 1500 J
- Volts: 125 V
- Plug type: NEMA 5-15P
- Outlets: 6
- Outlet type: NEMA 5-15R
- USB C charge ports: 1
- USB C output: 15W
- USB A charge ports: 1
- USB A output: 2.4A
- Total USB Output: 3.6A/18W
- EMI/RFI Filtration: Yes
- Warranty: One-Year Limited
- Connected Equipment Guarantee: \$100,000

SPECIFICATIONS

| INPUT | |
|--------------------------|----------------------|
| Input Plug Type | NEMA 5-15P |
| Input Voltage | 110 - 125 VAC |
| Maximum Input Current | 15 A |
| Plug Style | Wall-tap |
| OUTPUT | |
| Outlet Type | 6 x NEMA 5-15R |
| Outlets - Total | 6 |
| USB Charge Port | Yes |
| USB Charge Port Amperage | 3.6 A (Shared) |
| USB Charge Port Quantity | 2 |
| USB Charge Port Type | 1 Type A 1 Type C |
| USB Charge Port Voltage | 5 VDC |
| USB Charge Port Watts | 18 Watts |

| SURGE PROTECTION & FILTERING | |
|------------------------------|----------------------|
| Attenuation | 32 dB |
| Clamping Voltage | 600V (H-N, H-G, N-G) |
| EMI/RFI Filtration | Yes |
| Maximum Surge Current | 60,000 A |
| Maximum Surge Current H-G | 15,000 A |
| Maximum Surge Current H-N | 30,000 A |
| Maximum Surge Current N-G | 15,000 A |
| Maximum Surge Voltage | 6000 V |
| Response Time | <1 Nanosecond |
| Surge Suppression (Joules) | 1500 J |

P6WSUC

WALL-TAP SURGE PROTECTION

SPECIFICATIONS CONT.

| PHYSICAL | |
|------------------------------------------------|----------------------------|
| Color | White |
| Form Factors Supported | Direct Plug |
| Material of Construction | Plastic |
| PHYSICAL DIMENSIONS | |
| Physical Dimensions - Width/Height/Depth (cm) | 10.31 x 16.23 x 5.54 cm |
| Physical Dimensions - Width/Height/Depth (mm) | 103 x 162 x 55 mm |
| Physical Dimensions - Width/Height/Depth (in.) | 4.06 x 6.39 x 2.18 in. |
| Weight (kg) | 0.29 kg |
| Weight (lb) | 0.64 lbs. |
| SHIPPING DIMENSIONS | |
| Shipping Dimensions - Width/Height/Depth (cm) | 11.48 x 16.48 x 6.1 cm |
| Shipping Dimensions - Width/Height/Depth (mm) | 114.81 x 164.85 x 60.96 mm |
| Shipping Dimensions - Width/Height/Depth (in) | 4.52 x 6.49 x 2.4 in. |
| Weight (kg) | 0.38 kg |
| Weight (lb) | 0.84 lbs. |

| CERTIFICATIONS | |
|-------------------------------|---------------------------------------------------|
| Environmental | RoHS Compliant |
| Safety | UL1449 UL1310 UL498A cUL FCC DOE V |
| WARRANTY | |
| CEG Amount | \$100,000 |
| Connected Equipment Guarantee | Lifetime |
| Product Warranty | 1-Year Limited Warranty |