



PDU41104 SWITCHED PDU



Designed for datacenters and other electrically demanding applications.

The CyberPower PDU41104, a 0U rackmount switched power distribution unit (PDU), provides 200-240V 20A output via 21 IEC-320 C13 + 3 IEC-320 C19 receptacles from a single NEMA L6-20P input power plug. The switched outlet receptacles can be managed over the network by using the CyberPower Management Console, a web browser, and the RJ45 Ethernet port for network connection, or locally from the Power Control display. The PDU41104 offers outlets that can be turned on, turned off, or recycled on demand. Outlets can be programmed to address a number of needs including remote rebooting of locked equipment, load shedding, power sequencing, and locking out unauthorized loads.

With a three-year limited warranty, you can trust CyberPower's commitment to high quality.

TYPICAL APPLICATIONS

- Data Centers
- Network Closets
- VoIP Phone Systems

FEATURES

- Switched PDU
- Local and Network Outlet Switching
- SNMP Network Interface
- Controllable Receptacles
- Industrial-Grade Metal Housing
- Three-Year Limited Warranty

SPECIFICATIONS

GENERAL		OUTPUT	
Type	Switched	Nominal Output Voltage	200 - 240 V
Phase	Single Phase	Outlets - # of Banks	1
INPUT		Outlets - Total	24
Maximum Current	20A (Derated to 16A)	Outlets - Front	24
Frequency	50/60 Hz	Outlet Type	IEC-320 C13 (21) + C19 (3)
Plug Type	NEMA L6-20P	Meter Readout	Power Control Display
Cord Length (ft)	10	LED Indicators	Tx/Rx, LINK, Normal/Warning/ Critical Status

PDU41104 SWITCHED PDU

SPECIFICATIONS CONT.

MANAGEMENT & COMMUNICATIONS

Outlet switching	Yes
SNMP / HTTP Remote Monitoring	IPv4, TCP/IP, UDP, SNMPv1, HTTP, NTP, DNS, Telnet, DHCP, SMTP, FTP, IPv6, SNMPv3, HTTPs, SSH, SSL, TLS, LDAP(S), RADIUS, Syslog, CLI, Windows AD
Network Connection	RJ45 (Ethernet), RJ45 (COM Port)
Environmental Sensor	Optional, via RJ45
Modular Expandability (Cascading)	Yes, via RJ45
Updateable firmware	Yes, via USB or Ethernet
Modular Expandability (Cascading)	Yes, via RJ45
Updateable firmware	Yes, via USB or Ethernet
Multifunction LCD Screen	Voltage, Frequency, Load, Current, HW/FW Version, Network information

PHYSICAL

Standard Form Factor	0U
Style	Vertical Rackmount, Wallmount
Enclosure Construction	Steel
Cord Retention Tray/Cord Organizers	Yes
External Site Ground Pin	Yes
Dimensions - (WxHxD) (in)	2.2 x 65.5 x 1.9 (in)
Weight (lbs.)	17.2

ENVIRONMENTAL

Operating Temperature	32 °F to 140 °F (0 °C to 60 °C)
Operating Relative Humidity	0% - 95% Non-condensing
Maximum Operating Elevation	11,480 ft (3,500 m)

CERTIFICATIONS

Safety	UL 60950-1, FCC Class A
Environmental	RoHS Compliant

WARRANTY

Product Warranty	3 Years
------------------	---------