



## PDU15B4F8R Basic PDU

Engineered to distribute UPS, generator or utility AC power to equipment.

The CyberPower 12-outlet (4 Front/8 Rear) rack mount basic power distribution unit (PDU15B4F8R) provides 120V 15A output. It distributes power to 12 NEMA 5-15R receptacles from a single NEMA 5-15P plug, with unfiltered electrical pass-through.

Designed for datacenters and other electrically demanding applications, this unit has a rugged, industrial-grade metal housing and a 15-foot AC power cord. It can be mounted either horizontally or vertically, includes a cord retention tray and is ETL/RoHS certified.

A Lifetime Warranty ensures that this PDU is free of defects in design, assembly, material and workmanship.

### Typical Applications

- Servers
- Network Devices
- Telecom Equipment

### Features

- Basic PDU
- Switch-Free Design
- Industrial-Grade Metal Housing
- Lifetime Warranty

# PDU15B4F8R Basic PDU

Engineered to distribute UPS, generator or utility AC power to equipment.

| GENERAL                      |                                                                          |
|------------------------------|--------------------------------------------------------------------------|
| Type                         | Basic PDU                                                                |
| Phase                        | Single Phase                                                             |
| INPUT                        |                                                                          |
| Voltage                      | 120V                                                                     |
| Current                      | 15A max                                                                  |
| Frequency                    | 50Hz/60Hz                                                                |
| Plug Type                    | NEMA 5-15P                                                               |
| Plug Style                   | Straight                                                                 |
| Cord Length                  | 15'                                                                      |
| OUTPUT                       |                                                                          |
| Nominal Output Voltage       | 120V                                                                     |
| Outlets - Total              | 12                                                                       |
| Outlet Type                  | NEMA 5-15R                                                               |
| Outlets - Front              | 4                                                                        |
| Outlets - Rear               | 8                                                                        |
| Overload Protection          | 15A                                                                      |
| PHYSICAL                     |                                                                          |
| Rack Size                    | 1U                                                                       |
| Form Factors Supported       | 1U Rackmount, 0U Vertical Rackmount, Undercounter Installation Supported |
| Cord Retention Organizers    | Yes                                                                      |
| External Site Ground Pin     | Yes                                                                      |
| Adjustable Mounting Brackets | 2 sets (L-short, L-long)                                                 |
| Dimensions (WxHxD) (in.)     | 17.5 x 1.75 x 2.25                                                       |
| Weight (lbs.)                | 4.0                                                                      |
| ENVIRONMENTAL                |                                                                          |
| Operating Temperature        | 32°F to 95°F / 0°C to 35°C                                               |
| Operating Relative Humidity  | 0% - 95% non-condensing                                                  |
| Storage Temperature          | 5°F to 113°F / -15°C to 45°C                                             |
| Maximum Operating Elevation  | 10,000 ft / 3,000 m                                                      |
| Maximum Storage Elevation    | 50,000 ft / 15,000 m                                                     |
| CERTIFICATIONS               |                                                                          |
| Safety                       | UL1363 certified by ETL (USA), CSA C22.2 (Canada)                        |
| Environmental                | RoHS Compliant                                                           |
| WARRANTY                     |                                                                          |
| Product Warranty             | Lifetime                                                                 |