



JF-100RVG CPVC

2 Piece, Full Port, CPVC Connection, Stainless Steel Trim, Thermal Expansion Relief, 600 WOG

| PART NUMBER | SIZE | CASE | CARTON | WEIGHT |
|--------------|------|------|--------|--------|
| 105-080RVSSG | 3/4" | 12 | 1 | 16 |
| 105-100RVSSG | 3/4" | 12 | 1 | 16 |
| 105-125RVSSG | 3/4" | 12 | 1 | 16 |

- Dezincification Resistant Brass Alloy
- Side Discharge
- Available in 80, 100, 125 PSI
- Wetted Surfaces Contain Less than .25% Lead Content



CERTIFIED LEAD FREE



T-422G

2 Piece, Standard Port, Threaded x Expansion Pex Connection, Stainless Steel Trim, 400 WOG

| PART NUMBER | SIZE | CASE | CARTON | WEIGHT |
|--------------|--------|------|--------|--------|
| LEVER HANDLE | | | | |
| 104-523PG | 1/2" | 120 | 10 | 41 |
| 104-524PG | 3/4" | 100 | 10 | 51 |
| 104-525PG | 1" | 54 | 6 | 48 |
| 104-526PG | 1-1/4" | 36 | 6 | 49 |
| 104-527PG | 1-1/2" | 24 | 4 | 48 |
| 104-528PG | 2" | 12 | 2 | 40 |
| 104-529PG | 2-1/2" | 6 | 1 | 34 |
| 104-530PG | 3" | 6 | 1 | 61 |
| T-HANDLE | | | | |
| 104-523PG-TH | 1/2" | 120 | 10 | 35 |
| 104-524PG-TH | 3/4" | 100 | 10 | 40 |
| 104-525PG-TH | 1" | 54 | 6 | 40 |

- Dezincification Resistant Brass Alloy
- Gland Follower and Single O-Ring Stem Design
- Blow-Out Proof Stem
- 100% Leak Tested
- IAPMO Certified - NSF 61 & NSF 372 & NSF 14
- ASTM F1960
- Wetted Surfaces Contain Less than .25% Lead Content



LOW-LEAD
UPC
C
NSF/ANSI/CAN 61
NSF/ANSI/CAN 372
NSF/ANSI 14

CERTIFIED LEAD FREE



S-422G

2 Piece, Standard Port, Solder x Expansion Pex Connection, Stainless Steel Trim, 400 WOG

| PART NUMBER | SIZE | CASE | CARTON | WEIGHT |
|--------------|------|------|--------|--------|
| LEVER HANDLE | | | | |
| 104-533PG | 1/2" | 120 | 10 | 38 |
| 104-534PG | 3/4" | 100 | 10 | 47 |
| 104-535PG | 1" | 54 | 6 | 40 |
| T-HANDLE | | | | |
| 104-533PG-TH | 1/2" | 120 | 10 | 32 |
| 104-534PG-TH | 3/4" | 100 | 10 | 43 |

- Dezincification Resistant Brass Alloy
- Gland Follower and Single O-Ring Stem Design
- Blow-Out Proof Stem
- 100% Leak Tested
- IAPMO Certified - NSF 61 & NSF 372 & NSF 14
- ASTM F1960
- Wetted Surfaces Contain Less than .25% Lead Content



LOW-LEAD
UPC
C
NSF/ANSI/CAN 61
NSF/ANSI/CAN 372
NSF/ANSI 14

CERTIFIED LEAD FREE