

In-Wall PEX Supports

PEXRite® Flat Base Turn-Out PEX Support



- Turn-out support of 3/8 in. and 1/2 in. CTS PEX tubing
- Ideal for lavatory/sink and toilet stub-out and overhead 90-degree turn
- Mount to block of wood or other flat surface
- Unique design allows for side-entry of tubing

Part number	Size	Pipe size	Box qty
705	5-1/3 in. x 4-1/8 in. x 2-1/2 in.	3/8 in. - 1/2 in. CTS	50

90° Bend Support



- Rigid plastic bend support
- Provides rigid 90-degree bend for PEX tubing
- Compatible with all PEX tubing manufacturers

Part number	Size	Pipe size	Box qty
710	5-1/16 in. x 2-1/2 in. x 1 in.	1/2 in.	50
711	13-3/8 in. x 4-1/2 in. x 7-7/8 in.	3/4 in.	50

ProGuard™ Bend Support for PEX



- Prevents unwanted extreme turning radius that may cause PEX to kink
- Eliminates in wall fittings and concealed joints
- Flame Rated: UL 94 V-0
- Compatible with all manufacturers' 1/2 in. CTS PEX tubing

Part number	Pipe size	Box qty
734	1/2 in. CTS	50

In-Slab PEX Supports

703 Series In-Slab Stub-Up Support for PEX and Conduit



- Available in single and double pipe runs for multiple slab depths
- Multi-run versatility for manifolds with interlocking feet
- IAPMO PS 42-2013
- Material: Reinforced Polypropylene
- Fluid Temperature range: 32°F thru 200°F
- Temperature range: -10 °F to 120°F

Part number	Size	Pipe size	Box qty
703-SC	8.25 in. x 4 in. x 7.40 in.	1/2 in. PEX Tubing	20
703-DC	8.25 in. x 4 in. x 7.40 in.	1/2 in. PEX Tubing	20
703-SEC	8.25 in. x 4 in. x 7.40 in.	1/2 in. PEX Tubing	20
703-DEC	8.25 in. x 4 in. x 7.40 in.	1/2 in. PEX Tubing	20