

3M

Polyimide Tape

8997

Technical Data

January, 2015

Product Description 3M™ Polyimide Tape 8997 is an amber colored polyimide tape with silicone pressure sensitive adhesive. Tape construction is ideal for applications that may require high temperature, chemical, and abrasion resistance with the benefit of transparency.

Product Construction	Backing	Adhesive	Color	Standard Roll Length
	Polyimide	Silicone	Amber	36 yds. (33 m)

Typical Physical Properties **Note: The following technical information and data should be considered representative or typical only, and should not be used for specification purposes.**

		ASTM Test Method
Adhesion to Steel:	22 oz./in. width (24 N/100 mm)	D-3330
Tensile Strength:	26 lbs./in. width (453 N/100 mm)	D-3759
Elongation at Break:	37%	D-3759
Backing Thickness:	1.0 mils (0.025 mm)	D-3652
Total Thickness:	2.2 mils (0.057 mm)	D-3652
Temperature Use Range:	Up to 500°F (260°C)	

-
- Features**
- Polyimide films offer excellent thermal, abrasion, and chemical resistance while maintaining their flexibility.
 - Amber color makes tape placement obvious for both application and removal.
 - Thin backing leaves a sharp paint line and some conformability.
 - Silicone adhesives offer high heat resistance compared to many rubber and acrylic adhesives, reducing failure due to softening, oozing, and adhesive transfer.
 - Silicone adhesive removes cleanly from many surfaces.
 - Lined version available for die-cuts.

-
- Application Ideas**
- Masking parts for powder coat painting.
 - Masking edges of overlap seams in metal bonding process where excess adhesive flows onto tape. Minimizes clean-up on tape removal.
 - Provides a good barrier for separation of dissimilar metals.
-

3M Polyimide Tape

8997

Storage	Store under normal conditions of 60° to 80°F (16° to 27°C) and 40 to 60% relative humidity in the original packaging material.
Shelf Life	To obtain best performance, use this product within 24 months from date of manufacture.
Technical Information	The technical information, recommendations and other statements contained in this document are based upon tests or experience that 3M believes are reliable, but the accuracy or completeness of such information is not guaranteed.
Product Use	Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. Given the variety of factors that can affect the use and performance of a 3M product, user is solely responsible for evaluating the 3M product and determining whether it is fit for a particular purpose and suitable for user's method or application.
Warranty, Limited Remedy, and Disclaimer	Unless an additional warranty is specifically stated on the applicable 3M product packaging or product literature, 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. If the 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.
Limitation of Liability	Except where prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.

ISO 9002

This Industrial Adhesives and Tapes Division product was manufactured under a quality system registered to ISO 9001:2000 standards.



Industrial Business
Industrial Adhesives and Tapes Division
3M Center, Building 225-3S-06
St. Paul, MN 55144-1000
800-362-3550 • 577-369-2923 (Fax)
www.3M.com/IATD

Recycled Paper
40% pre-consumer
10% post-consumer

3M is a trademark of 3M Company.
Printed in U.S.A.
©3M 2015 (1/15)