

**ProLine**<sup>®</sup>  
SERIES



ProLine<sup>®</sup> FlexConnect Appliance Connectors provide a safe and easy method to install household appliances such as gas ranges, water heaters, furnaces and more. The durable, stainless-steel construction supports high flow rates, wide temperature ranges and is resistant to corrosive water and environmental conditions. In addition, each connector is 100% leak tested to ensure the highest quality. ProLine<sup>®</sup> FlexConnect Appliance Connectors include a full range of yellow epoxy-coated and stainless steel gas connectors as well as stainless steel water connectors.

A BRAND OF MUELLER INDUSTRIES



FLEXIBLE CONNECTORS



## WATER CONNECTORS • FLEXCONNECT™ STAINLESS STEEL

Item No.	Connections	Available Lengths						
<b>3/4" ID</b>								
W034SS1010__	3/4" F x 3/4" F	12"	15"	18"	24"	36"	48"	
W034SS1011__	3/4" F x 3/4" M	12"	15"	18"	24"	36"	48"	
W034SS1012__	3/4" F x 1" F	12"	15"	18"	24"	36"	48"	
W034SS1013__	3/4" F x 1-1/4" F	12"	15"	18"	24"	36"	48"	
W034SS1050__	3/4" F x 3/4" PUSH-FIT	12"	15"	18"	24"	36"	48"	
	<b>Carton QTY</b>	<b>25</b>	<b>25</b>	<b>25</b>	<b>25</b>	<b>25</b>	<b>25</b>	
<b>1" ID</b>								
W100SS1212__	1" F x 1" F	12"	15"	18"	24"			
W100SS1213__	1" F x 1-1/4" F	12"	15"	18"	24"			
<b>1-1/4" ID</b>								
W114SS1313__	1-1/4" F x 1-1/4" F	12"	15"	18"	24"			
<b>1-1/2" ID</b>								
W112SS1414__	1-1/2" F x 1-1/2" F	12"	15"	18"	24"			
<b>2" ID</b>								
W200SS1515__	2" F x 2" F	12"	15"	18"	24"			
	<b>Carton QTY</b>	<b>12</b>	<b>12</b>	<b>12</b>	<b>12</b>			





## PART NUMBER SCHEMATICS FLEXIBLE CONNECTORS

GAS CONNECTOR EXAMPLE					
1	2	3	4	5	6
<b>G</b>	<b>012</b>	<b>SS</b>	<b>10</b>	<b>11</b>	<b>36</b>
Gas	1/2" OD	Stainless	1/2" MIP	1/2" FIP	36" Length

CHARACTER 1: APPLICATION	
<b>G</b>	Gas

CHARACTER 2: DIAMETER OF CONNECTOR	
<b>014</b>	1/4" ID (3/8" OD)
<b>038</b>	3/8" ID (1/2" OD)
<b>012</b>	1/2" ID (5/8" OD)
<b>034</b>	1" ID (7/8" OD)

CHARACTER 3: COATING	
<b>SS</b>	Stainless Steel
<b>YE</b>	Yellow Epoxy Coated

CHARACTER 4 & 5: FITTING OR VALVE CONNECTIONS (CHOOSE 2)	
<b>10</b>	1/2" MIP (Tapped 3/8" FIP)
<b>11</b>	1/2" FIP
<b>12</b>	3/8" MIP (Tapped 1/4" FIP)
<b>13</b>	3/8" FIP
<b>14</b>	3/4" MIP (Tapped 1/2" FIP)
<b>15</b>	3/4" FIP
<b>16</b>	1" MIP (Tapped 1/2" FIP)
<b>17</b>	1" FIP
<b>21</b>	3/4" FIP Elbow
<b>31</b>	1/2" FIP Ball Valve
<b>33</b>	3/4" FIP Ball Valve
<b>41</b>	1/2" FIP Angle Valve
<b>43</b>	3/4" FIP Angle Valve

CHARACTER 6: NOMINAL LENGTH IN INCHES							
12	18	24	30	36	48	60	72

WATER CONNECTOR EXAMPLE					
1	2	3	4	5	6
<b>W</b>	<b>034</b>	<b>SS</b>	<b>10</b>	<b>11</b>	<b>18</b>
Water	3/4" OD	Stainless	3/4" FIP	3/4" MIP	18" Length

CHARACTER 1: APPLICATION	
<b>W</b>	Water

CHARACTER 2: DIAMETER OF CONNECTOR	
<b>034</b>	3/4" ID
<b>100</b>	1" ID
<b>114</b>	1-1/4" ID
<b>112</b>	1-1/2" ID
<b>200</b>	2" ID

CHARACTER 3: COATING	
<b>SS</b>	Stainless Steel

CHARACTER 4 & 5: FITTING OR VALVE CONNECTIONS (CHOOSE 2)	
<b>10</b>	1/2" MIP (Tapped 3/8" FIP)
<b>11</b>	1/2" FIP
<b>12</b>	3/8" MIP (Tapped 1/4" FIP)
<b>13</b>	3/8" FIP
<b>14</b>	3/4" MIP (Tapped 1/2" FIP)
<b>15</b>	3/4" FIP
<b>16</b>	1" MIP (Tapped 1/2" FIP)
<b>17</b>	1" FIP
<b>21</b>	3/4" FIP Elbow
<b>31</b>	1/2" FIP Ball Valve
<b>33</b>	3/4" FIP Ball Valve
<b>41</b>	1/2" FIP Angle Valve
<b>43</b>	3/4" FIP Angle Valve

CHARACTER 6: NOMINAL LENGTH IN INCHES							
12	15	18	24	36	48		

\* Nut x Nut connectors are not CSA design certified.