

# CyberPower

## PBJ5UC PREMIUM SURGE PROTECTOR

Protect home and office computers, electronics, and home theater equipment

The CyberPower Premium Surge Protector PBJ5UC is ideal for the home, office, or home theater because it is designed to provide maximum protection and convenience to a number of devices where wall receptacles are out of reach. The Premium Surge Protector prevents damaging spikes in energy caused by storms and electrical power from reaching your electronic equipment. The PBJ5UC provides 3,480 joules of protection, 12 outlets (6 widely-spaced for transformer plugs), 4 USB charging ports, and a right-angle, 5-foot braided power cord.

Features of the PBJ5UC include safe-fail notification and fireproof technology. This surge suppressor comes with a One-Year Limited warranty and a connected equipment guarantee.

### TYPICAL APPLICATIONS

- Mobile Devices
- Personal Electronics
- Cell Phones
- Personal Computers

### FEATURES

- Surge suppression: 3,480 J
- Volts: 125 V
- Circuit breaker: 15 A
- Plug type: NEMA 5-15P (45° offset)
- Outlet type: 12 x NEMA 5-15R (surge-protected)
- Transformer outlets: 6
- Power cord: 5 ft.
- Data line protection: Coaxial, Network
- Cable/Satellite protection: Yes
- EMI/RFI Filtration: Yes
- Warranty: One-Year Limited
- Connected Equipment Guarantee: \$1,000,000



## SPECIFICATIONS

INPUT	
Circuit Breaker	15 A
Cord Length	5 ft (1.5 m)
Input Plug Type	NEMA 5-15P
Maximum Input Current	15 A

OUTPUT	
Outlet Type	12 - NEMA 5-15R
Outlets - Total	12
Outlets - Widely-Spaced	6
USB Charge Port	Yes
USB Charge Port Amperage	4.8 Amps (Shared)
USB Charge Port Quantity	4
USB Charge Port Type	4 Type A
USB Charge Port Voltage	5 VDC

# PBJ5UC

## PREMIUM SURGE PROTECTOR

### SPECIFICATIONS CONT.

#### SURGE PROTECTION & FILTERING

Attenuation	43 dB
Clamping Voltage	500V (H-N, H-G, N-G)
Coax Protection RG6	2 in 2 out Tin
EMI/RFI Filtration	150 KHz - 100 MHz
Maximum Surge Current	105,000 A
Maximum Surge Current H-G	15,000 A
Maximum Surge Current H-N	75,000 A
Maximum Surge Current N-G	15,000 A
Maximum Surge Voltage	6,000 V
Network Protection RJ45	1 in / 1 out
Response Time	<1 Nanosecond
Surge Suppression (Joules)	3,480 J

#### MANAGEMENT & COMMUNICATIONS

LED Indicators	Clean Power Ground LED
----------------	---------------------------

#### PHYSICAL

Color	Black
Form Factor	Strip
Form Factors Supported	Keyhole (Wall Mount or Under-counter Installation)
Material of Construction	Plastic
Safety Covers	No

#### DIMENSIONS

Physical Dimensions - WxHxD (cm)	13.41 x 3.66 x 32.72 cm
Physical Dimensions - WxHxD (mm)	134 x 37 x 327 mm
Physical Dimensions - WxHxD (in.)	5.28 x 1.44 x 12.88 in.
Weight (kg)	0.97 kg
Weight (lb)	2.13 lbs.

#### SHIPPING DIMENSIONS

Shipping Dimensions - WxHxD (cm)	4.45 x 40.64 x 19.35 cm
Shipping Dimensions - WxHxD (mm)	44.45 x 406.4 x 193.55 mm
Shipping Dimensions - WxHxD (in)	1.75 x 16.0 x 7.62 in.
Shipping Weight (kg)	1.09 kg
Shipping Weight (lbs.)	2.40 lbs.

#### CERTIFICATIONS

Environmental	RoHS Compliant
Safety	UL1363 UL1310 UL1449 4th Edition cUL FCC DOE VI

#### WARRANTY

CEG Amount	\$1,000,000
Connected Equipment Guarantee	Lifetime
Product Warranty	One-Year Limited