

YOUR AUTHORIZED CONTINENTAL DEALER



GAS FURNACES

C95 SERIES

HIGH EFFICIENCY SINGLE STAGE

CONTINENTAL

P: 1-866-820-8686
continentalcomfort.com



Consult your owner's manual for complete installation instructions, accurate framing dimensions and proper clearances to combustible material. Check all local and national building codes. All specifications are subject to change without prior notice due to on-going product improvements. Products may not be exactly as shown.

Build Quality, Build Confidence.
continentalcomfort.com



CONTINENTAL

C95 SERIES

Truly Reliable

WHISPER QUIET™ Soft Start Motor

With a Whisper Quiet™ operation the EnerSave Plus and EnerSave Pro motors will 'soft start' & 'soft stop' gradually changing speed to reduce the noise created by conventional motors.

WiFi Capable

Our furnaces are compatible with any 24V thermostat, including Wifi connected thermostats.

Patented Vortex™ Technology

Vortex™ turbulator inside the heat exchanger increases efficiency by disrupting the natural airflow which extracts the maximum heat from the flue gases.

FEATURES

- 30,000 - 100,000 BTU models available
- Models feature a multi-speed motor with reduced electrical consumption
- Self-diagnostic integrated furnace control (IFC)
- Manufactured for Natural Gas, Propane conversion kit available
- Single stage heating
- Flexfit™ - Upflow, right, left, down
- Lifetime heat exchanger warranty



EFFICIENT TECHNOLOGY:

Continental C95 Series WPX models feature a multi-speed motor which drastically reduces energy consumption when compared to a traditional PSC motor.



MULTI-POSITION INSTALLATION

Upflow, horizontal and downflow for versatile installations.



SPECIFICATIONS

MODEL	WPX030S2AA-C	WPX040S2AA-C	WPX060S3AA-C	WPX080S3AA-C	WPX100S5BA-C
HEATING CAPACITIES					
Efficiency (AFUE)	95%	95%	95%	95%	95%
Input High Fire (BTU/H)	30,000	40,000	60,000	80,000	100,000
DIMENSIONS					
Height (in)	34	34	34	34	34
Depth (in)	29 ½	29 ½	29 ½	29 ½	29 ½
Width (in)	17 ½	17 ½	17 ½	17 ½	22 ½
Weight (lbs)	121	124	131	134	163
FURNACE CAPACITY					
CFM High Fire*	495	691	921	1320	1581
Return Air (in)	14 X 23				
AIRFLOW AND COOLING					
Motor Size	1/3 hp	1/2 hp	1/2 hp	1/2 hp	1 hp



**PARTS AND
UNIT REPLACEMENT**
LIMITED WARRANTY