



4700 W. 160th St.
Cleveland, OH 44135
PH:800-321-9532
FX:800-321-9535
www.oatey.com

TECHNICAL SPECIFICATION

CABLE, CONDUIT & DUCT TIES



TECHNICAL SPECIFICATION: Oatey Cable, Conduit and Duct Ties provide a fast and convenient method for securing a variety of components in place. Cable, Conduit and Duct Ties are designed with a locking device to provide a positive, non-slip for fastening all types of loose items.



APPROVALS AND LISTINGS

Meet Military Standard MS3367-1 for dimensions and Military Standard M-20693 for material.

PHYSICAL/CHEMICAL PROPERTIES

Material 6/6 Nylon
Color Natural (7" – 36")
Gray (48")
Tensile Strength 7", 11" 14" = 50 lbs.
24", 36", 48" = 175 lbs.

DIRECTIONS FOR USE

Wrap tie around components and lock in place with locking device. Check with local codes to ensure proper spacing requirements for piping support.

PRECAUTIONS

Read cautions and directions on packaging carefully before using this product. KEEP OUT OF REACH OF CHILDREN.

COMMON APPLICATIONS

Oatey Cable, Conduit and Duct Ties provide a fast and convenient method for securing a variety of components in place.

Consult Oatey Technical Department for applications not specifically referenced above.

PRODUCT NUMBER	DESCRIPTION	PACK	CARTON WEIGHT
33850	7-½" Ties for 1-¾" diameter (25 per bag)	12 bags	2 lbs.
33851	11" Ties for 3" diameter (25 per bag)	12 bags	2 lbs.
33852	14" Ties for 4" diameter (25 per bag)	12 bags	3 lbs.
33853	24" Ties for 7" diameter (6 per bag)	12 bags	4 lbs.
33854	34" Ties for 10" diameter (6 per bag)	12 bags	4 lbs.
33855	48" Ties for 15" diameter (6 per bag)	12 bags	5 lbs.