



B1206 | ESSENTIAL SURGE PROTECTOR

Protect home and office computers, electronics, and home theater equipment

The CyberPower B1206 12-outlet surge protector offers a high level of surge protection for common home and office electronics such as computers and peripherals, home theater equipment, and appliances. With 3000 joules of surge protection, the B1206 prevents power surges and power spikes caused by storms and electrical grid fluctuations from reaching and potentially harming your valuable electronic equipment. The B1206 comes with 12 standard, grounded power outlets and a six-foot power cord with a low-profile grounded plug which fits tightly against walls for unimpeded placement behind furniture.

Features of the B1206 include automatic shutdown, metal oxide varistor (MOV) technology, an EMI/RFI noise filter, keyhole mounting slots, and impact-resistant casing. This surge suppressor comes with a Limited Lifetime Warranty and a Connected Equipment Guarantee.

TYPICAL APPLICATIONS

- Personal Computers
- Chargers
- Personal Electronics

FEATURES

- AC Outlets: 12
- AC Outlet Type: NEMA 5-15R
- Surge Protection: 3,000 Joules
- Cord Length: 6 ft
- Plug Type: NEMA 5-15P
- Plug Style: Flat
- Electrical Rating: 125V/15A/60Hz
- Connected Equipment Guarantee: \$300,000
- Warranty: Lifetime Limited Warranty



SPECIFICATIONS

INPUT	
Circuit Breaker	15 A
Cord Length	6 ft (1.8 m)
Input Plug Type	NEMA 5-15P
Maximum Input Current	15 A
Plug Style	45° Offset Right
OUTPUT	
Outlet Type	12 - NEMA 5-15R
Outlets - Total	12

SURGE PROTECTION & FILTERING	
Attenuation	32 dB
Clamping Voltage	600V (H-N, H-G, N-G)
EMI/RFI Filtration	150 KHz / 100 MHz / Yes
Maximum Surge Current	90,000 A
Maximum Surge Current H-G	15,000 A
Maximum Surge Current H-N	60,000 A
Maximum Surge Current N-G	15,000 A
Maximum Surge Voltage	6,000 V
Response Time	<1 Nanosecond
Surge Suppression (Joules)	3,000 J

B1206

ESSENTIAL SURGE PROTECTOR

SPECIFICATIONS CONT.

PHYSICAL	
Color	Black
Form Factors Supported	Keyhole (Wall Mount or Under-counter Installation)
Material of Construction	Plastic
DIMENSIONS	
Physical Dimensions - Width/Height/Depth (cm)	10.41 x 4.04 x 30.56 cm
Physical Dimensions - Width/Height/Depth (mm)	104 x 40 x 306 mm
Physical Dimensions - Width/Height/Depth (in.)	4.1 x 1.59 x 12.03 in.
Weight (kg)	0.68 kg
Weight (lbs.)	1.50 lbs.

SHIPPING DIMENSIONS	
Shipping Dimensions - Width/Height/Depth (cm)	15.88 x 36.2 x 5.08 cm
Shipping Dimensions - Width/Height/Depth (mm)	158.75 x 361.95 x 50.8 mm
Shipping Dimensions - Width/Height/Depth (in.)	6.25 x 14.25 x 2 in.
Shipping Weight (kg)	0.73 kg
Shipping Weight (lbs.)	1.75 lbs.
CERTIFICATIONS	
Environmental	RoHS Compliant
Safety	UL1363, UL1449 4th Edition, UL1310, cUL, FCC PART 15B, ICES-003, DOE VI, NRCan
WARRANTY	
CEG Amount	\$300,000
Connected Equipment Guarantee	Lifetime
Product Warranty	Limited Lifetime Warranty