

The StarLink® SLE-ANTEX Series are optional marine-grade exterior antennae, that dramatically increase cellular transmission capability and enable location flexibility, for use with StarLink Cell/IP Communicator models, as well as universally supporting most other brand radios, including Honeywell®, DSC®, DMP®, etc. The maximum performance, omnidirectional wide band antenna, can be used to increase signal strength in all applications and cellular technologies: LTE, 4G, 3G, CLR, PCS, DCS, AWS, IMT, ISM, WCDMA, cellular, WiFi and WiMax. With LTE performance in particular, the antenna has excellent field-proven performance at 700 MHz.

All feature a compact, long-life UV-stable polyurethane conical shape antenna and physically resonant design; average gain of 4-9dBi and outstanding low VSWR of less than 1.5:1, for maximum radiated power and maximum signal range. Sold complete, each SLE-ANTEX Series extended range antenna includes an L-bracket with stainless steel U-bolts for pole or wall mounting, and premium low-loss cable, available in choice of 3 lengths, 75', 50' or 30', respectively, to connect to the StarLink or other brand Cell/IP communicator.



FEATURES:

- Increase Cellular Transmission & Mounting Flexibility
- Universal use with StarLink Cellular Communicators & Those of other manufacturers
- For Outdoor Use - Marine Grade
- All Applications: LTE, 4G, 3G, CLR, PCS, DCS, AWS, IMT, ISM, WCDMA, cellular, WiFi and WiMax
- Excellent 700MHz LTE performance
- VSWR <1.5:1 for max power and signal range
- RoHS Compliant
- 36-Month Napco Warranty
- Complete: Including Mounting Hardware & 30', 50' or 75' cable

ORDERING INFORMATION:

SLE-ANTEXT75 Optional extended antenna with 75' cable (22.86m)

SLE-ANTEXT50 As above, with 50' cable

SLE-ANTEXT30 As above, with 30' cable

SPECIFICATIONS:

- Radiation Pattern:** Omni-Directional
- Gain:** 4-9dBi
- Bandwidth:** VSWR: <1.5: 1 = 695-3000 MHz in all 3G & 4G Bands
- Bandwidth:** VSWR: <2.0: 1 = 695-3000 MHz
- Impedance:** 50 ohms
- Max Input Power:** 50 watts
- Exterior Finish:** Black or white UV stable
- Dimensions:** 8 7/8" (225 mm) l x 2 3/8" (60 mm) od
- Weight:** Varies with model, cable length chose
- RF Connector:** Type N female
- PIM:** 155dBc
- Cable:** Low-loss cable with premium connectors & mounting hardware
- Installation:** Included L Bracket with U-bolts for up to 2" pole
- Elements:** Copper
- Polarization:** Vertical
- Wind Rating:** >110 MPH
- Warranty:** 3 years
- Compliance:** RoHS

Extended Range Cell Antenna for use with All StarLink Models & Most Competitive Brands

