CyberPower

P205UCQ | HOME OFFICE SURGE PROTECTORS

Protect home and office computers, electronics, and home theater equipment

The CyberPower P205UCQ brings you power, protection, and versatility – all in one compact unit. Featuring two AC power outlets with 1,500J of surge protection, 1 USB-A charging port, one USB-C charging port, and a 10W wireless Qi charging pad that works with iPhone and Android phones. It's perfect for desk tops, table tops or other high-traffic areas of the home or office.



- Personal Electronics
- Wireless Speakers
- Cell Phones
- Tablets

FEATURES

- Surge suppression: 1,500 J
- Outlet type: NEMA 5-15R
- Outlet quantity: 2
- Total USB Output: 18W
- USB-C charge ports: 1
- USB-C charge output: 15W (shared)
- USB-A charge ports: 1
- USB-A charge output: 2.4A (shared)
- Wireless Charging: Qi 10W
- Power cord length: 5 ft
- Power cord type: braided
- Plug style: Right-angle 45° offset
- Volts: 125 V

Protected

- Warranty: 1-Year Limited
- Connected Equipment Guarantee: \$100,000



INPUT	
Circuit Breaker	None
Cord Length	5 ft (1.5 m)
Input Plug Type	NEMA 5-15P
Input Voltage	110 - 125 VAC
Maximum Input Current	15 A
Plug Style	Right Angle - 45° Offset

OUTPUT		
Outlet Type	2 - NEMA 5-15R	
Outlets - Total	2	
USB Charge Port	Yes	
USB Charge Port Amperage	2.4 A (Shared)	
USB Charge Port Quantity	2	
USB Charge Port Type	1 Type A 1 Type C	
USB Charge Port Voltage	5 VDC	
USB Charge Port Watts	15 Watts	
Wireless Charging	Yes	
Wireless Charging Output	10 W	
Wireless Charging Type	Qi Certified	

P205UCQ HOME OFFICE SURGE PROTECTORS

SPECIFICATIONS - CONT.

SURGE PROTECTION & FILTERING		
Clamping Voltage	600V (H-N, H-G, N-G)	
Coax Protection RG6	None	
EMI/RFI Filtration	No	
Maximum Surge Current	15,000 A	
Maximum Surge Current H-G	N/A	
Maximum Surge Current H-N	15,000 A	
Maximum Surge Current N-G	N/A	
Maximum Surge Voltage	6,000 V	
Response Time	<1 Nanosecond	
Surge Suppression (Joules)	1,500 J	
PHYSICAL		
Color	White	
Form Factors Supported	Horizontal Mount in Variety of Other Applications	
Material of Construction	Plastic	
PHYSICAL DIMENSIONS		
Physical Dimensions - Width/Height/Depth (cm)	8.41 x 4.29 x 8.41 cm	
Physical Dimensions - Width/Height/Depth (mm)	84 x 43 x 84 mm	
3	84 x 43 x 84 mm 3.31 x 1.69 x 3.31 in.	
Width/Height/Depth (mm) Physical Dimensions -		

SHIPPING DIMENSIONS		
Shipping Dimensions - Width/Height/Depth (cm)	13.34 x 16.26 x 8.38 cm	
Shipping Dimensions - Width/Height/Depth (mm)	133.35 x 162.56 x 83.82 mm	
Shipping Dimensions - Width/Height/Depth (in)	5.25 x 6.4 x 3.3 in.	
Weight (kg)	0.68 kg	
Weight (lb)	1.50 lbs.	
CERTIFICATIONS		
Environmental	RoHS Compliant	
Safety	UL1449 UL2738 UL1310 FCC cUL DOE VI	
WARRANTY		
CEG Amount	\$100,000	
Connected Equipment Guarantee	Lifetime	
Product Warranty	1-Year Limited Warranty	