



## Safety

See safety datasheet (if applicable) and product label for safety information, handling and proper use.

## Directions for Use

RECOMMENDED FOR: Wood; Ceramic Tile; Terrazzo; Marble; Magnesite; Concrete; Glazed Tile; Synthetic Sports Floors; Sealed or Painted Surfaces; Formica Walls or Counters; Aluminum or Stainless Steel; Furniture and Fixtures; Lockers and File Cabinets; Sealed Masonry Surfaces. DIRECTIONS: DUST MOP AND CLOTH TREATMENT: Sprinkle or apply coarse spray treatment directly on mops or cloths. Before using mops hang overnight with wicks down. On new or freshly laundered mops -- apply 2 ounces per linear foot of dust mop. Daily care: Shake out dust and spread wicks apart, then retreat with 1 ounce per linear foot. Hang treated mop in well-ventilated area until next day's use. Do not overtreat mop. Heavily soiled cloths or dust mops should be laundered and retreated.

## Certifications

Classified by Underwriters Laboratories, Inc. as to slip resistance. (186S).

A high-quality dust mop treatment formulated to clean and protect seals and finishes. Daily dust mopping with Super Hil-Tone increases the life and beauty of your floors by reducing the abrasive effects of tracked in dirt. Treatment with Super Hil-Tone provides excellent resistance to black heel marks, scuffing, and scratching.

## Features & Benefits

Formulated to clean and protect seals and finishes

Increases the life and beauty of floors to keep them looking great

Reduces the abrasive affects of tracked in dirt

## Item Number & Unit of Measure

Item Number	HIL0021507
Unit of Measure	5 gal Pail

## Specifications

Color	Light Yellow
Appearance	Clear to Slightly
Fragrance	Oil
Formula Type	Liquid
Dilution Ratio	RTU
PH	N/A
Non-Volatile Matter	95.00 - 97.50%
UL Certified	Yes