





# SEIGER / BAUER / GRACE

46 INCH LAUNDRY CABINET with FAUCET and DUAL STAINLESS SINK
MODEL # AXCLDYSEI-40









# Questions, problems, assembly help, missing parts?

No need to return the product, we will gladly help and ship your replacement parts free of charge

Please call Customer Service at 1-866-518-0120 ext. 262 Monday to Friday between 9 am – 4 pm EST or go to

### www.simpli-home.com/parts request

If you wish to return the product, please contact the retailer where the	
Purchased at	Date of Purchase
Model #	Part Number or Letter
In order to assist you in a timely manner, please have the following information ready:	

product was purchased.

2/32

**IMPORTANT:** Please read this manual carefully before beginning assembly of this product. Keep this manual for future reference.

# **SAFETY INFORMATION**

Identify all the parts and hardware. Do not discard the packaging until you have checked that you have all of the parts and hardware required. Hardware package may have spare parts.

**WARNING:** This item contains small parts which can be swallowed by children and pets. Keep children and pets away during assembly. To avoid danger of suffocation, always keep plastic bags away from children and pets. We recommend that you assemble this unit on a carpeted floor to avoid scratches. We do not recommend the use of power tools for assembly as this could damage the unit. Only use manual tools.


Requires 2 people for ease of assembly.

# **CARE and MAINTENANCE**


To clean, use a soft or slightly damp cloth, then wipe with a clean, drycloth. Dust with a soft dry cloth.

Do not use ammonia-based cleaning products, as they will damage the finish. Do not leave liquids or damp cloths on this furniture.

To avoid dulling of the finish, do not place this furniture in direct sunlight. Please inspect and tighten all screws or bolts on a regular basis to ensure proper performance and safety of your item.




4/32




NEED HELP? For help with assembly or if you are missing a part,

Please call customer service at 1-866-518-0120 ext. 262 (9 am to 4 pm EST)




6/32




NEED HELP? For help with assembly or if you are missing a part,


Please call customer service at 1-866-518-0120 ext. 262 (9 am to 4 pm EST)





NOTE: THE SCREWDRIVER IS NOT INCLUDED IN THE HARDWARE PACK.






Screw Cam Pins (II) into the pre-drilled small holes on Left Panel (F) and Right Panel (B). Let Self-Tapping Screw (IV) M4x16 go through the hole of Slide Rail (VII), then screw into the small hole of Left Panel (F).




NOTE: THE SCREWDRIVER IS NOT INCLUDED IN THE HARDWARE PACK.



Screw Cam Pins (II) into the pre-drilled small holes on Middle Panel (J). Let Self-Tapping Screw (IV) M4x16 go through the hole of Slide Rail (VII), then screw into the small hole of Middle Panel (J).




NOTE: THE SCREWDRIVER IS NOT INCLUDED IN THE HARDWARE PACK.



Screw Cam Pins (II) into the pre-drilled small holes on Bottom Panel (A) and Back Middle Panel (E).

STEP 4





Insert Wood Dowels (III) into the pre-drilled hole of Middle Panel (J). Attach Middle Panel (J) to Back Middle Panel (E) and Bottom Panel (A). Insert Cam Locks (I) into pre-drilled holes on Middle Panel (J). Tighten with flathead screwdriver.



NOTE: THE SCREWDRIVER IS NOT INCLUDED IN THE HARDWARE PACK.








Insert Wood Dowels (III) into the pre-drilled hole of Front Top Panel (I) and (H). Attach Middle Panel (J) to Front Top Panel (I) and (H).

Insert Cam Locks (I) into the pre-drilled hole of Top Panel (I) and (H). Tighten with flathead screwdriver.



NOTE: THE SCREWDRIVER IS NOT INCLUDED IN THE HARDWARE PACK.




Insert Wood Dowels (III) into the pre-drilled holes of Bottom Panel (A), Front Top Panel (H) and (I), Back Bottom Panel (C), Back Middle Panel (E) and Back Top Panel (D).


Attach Bottom Panel (A), Front Top Panel (H) and (I), Back Bottom Panel (C), Back Middle Panel (E), Back Top Panel (D) to Right Side Panel (B) and Left Side Panel (F).

Insert Cam Locks (I) into pre-drilled holes on Bottom Panel (A), Front Top Panel (H) and (I), Back Bottom Panel (C), Back Middle Panel (E), Back Top Panel (D). Tighten with flathead screwdriver.




NOTE: THE SCREWDRIVER IS NOT INCLUDED IN THE HARDWARE PACK.






Screw Cam Pins (II) into the pre-drilled small holes on Kick Plate Panel (G). Insert Cam Pins (II) into the pre-drilled holes on both Side Panels. Insert Cam Locks (I) into pre-drilled holes on both Side Panels. Tighten with flathead screwdriver.



Let Self-Tapping Screws M4X25 go though the hole of Top Front Panel and screw into Top Panel (K).




NOTE: THE SCREWDRIVER IS NOT INCLUDED IN THE HARDWARE PACK.



Use Phillips Screwdriver to attach the Right Door hinges with Self-Tapping Screw (IV) M4x16. Use Phillips Screwdriver to attach the Left Door hinges with Self-Tapping Screw (IV) M4x16.




NOTE: THE SCREWDRIVER IS NOT INCLUDED IN THE HARDWARE PACK.



Let Self-Tapping Screws M4x25 go though the hole of Top Front Panel and screw into the Drawer Panel (M).



NOTE: THE SCREWDRIVER IS NOT INCLUDED IN THE HARDWARE PACK.




Insert Dowels into the holes of Drawer Front (N) and Drawer Back (O).

Attach Drawer Left (P) to Drawer Front (N) and Drawer Back (O).

Use Phillips Screwdriver to attach the Drawer Left (P) with Self-Tapping Screw (IV) M4x40.






Put the Drawer Bottom into the slot of the Drawer Front (M), Drawer Back (O) and Drawer Left (P). Attach Drawer Right (P) to Drawer Front (M) and Drawer Back (O).


Use Phillips Screwdriver to attach the Drawer Right (P) with Self-Tapping Screw (IV) M4x40.

STEP 13




Use Phillips Screwdriver to attach the Slide Rail (VIII) with Self-Tapping Screw (IV) M4x40 and screw Self-Tapping Screw (IV) M4x16 into the holes of Drawer Left (P) and Drawer Right (P).

STEP 14




Place the Drawer into the cabinet.



Let Self-Tapping Screws M4X25 go though the hole of Drawer Front and screw into Drawer Panel (M).




NOTE: THE SCREWDRIVER IS NOT INCLUDED IN THE HARDWARE PACK.



Use Phillips Screwdriver to screw the Handle (VI) with Pan Head Philips Screws (V) M4x30.

# **ASSEMBLY**


# MODEL # AXCLDYSEI-40




Place a Rubber Washer (BB) onto the end of the Faucet (AA) and insert the Faucet through the top of the Sink (R).

From underneath the Sink (R), secure the Faucet (AA) to the Sink (R) using a Rubber Washer (BB), Steel Washer (CC) and Brass Nut Assembly (DD).


Insert Faucet Sealing Ring (EE) into hole of the pipe and screw hose pipe into it.



Attach the Weight Block (FF) to the pipe and screw together.



Place the Sink (R) with the attached Faucet (AA) on top of the cabinet.



Put the Drain Washer (3) on the top of the drain opening in the Sink (R).
Put the Drain Bowl (2) on the Drain Washer (3) through the drain opening.
From underneath the sink fasten the Threaded Washer (4) onto the Drain Bowl (2) and tighten.
Insert the Drain Plug (1) into the Drain Bowl (2).


# **ASSEMBLY**

### MODEL # AXCLDYSEI-40

### STEP21



NOTE: THE ADJUSTABLE WRENCH IS NOT INCLUDED IN THE HARDWARE PACK.




Fasten the nuts of the hoses (not included in package) to the nut ends of the faucet body. Fasten the nuts of the hoses (not included in package) to the water outlet:

- Red striped hose to Hot water supply
- o Blue striped hose to Cold water supply

Ensure to only tighten the nut and not twist the supply hose.

Leakage may occur if hoses are twisted.



Put a Pipe Washer (5) onto the Straight Drain Pipe (7).

Connect the Straight Drain Pipe (7) to the drain and fasten the Coupling (6).

Put the Coupling (8) into the Straight Drain Pipe (7) and put a Pipe Washer (9) into the Straight Drain Pipe (7).


Connect the Drain Channel (10) to the Straight Drain Pipe (7) and fasten with the Coupling (8).

On the Drain Channel (10), wrap teflon tape (not included) around the threaded end that connects to the Outer Drain Channel (12).

Connect the Outer Drain Channel (12) to the Drain Channel (10) and fasten with the Coupling (8). Insert the Outer Drain Channel (12) into the Drain Channel (10) and cover with the Pipe Cover (11).



NOTE: THE SCREWDRIVER IS NOT INCLUDED IN THE HARDWARE PACK.



Use a Phillips screwdriver to re-align or adjust the hinges that attach the doors to the cabinet.





### **WARRANTY**

Thank you for purchasing a **Simpli Home – Wyndenhall – Brooklyn + Max** product. These products have been made to demanding, high-quality standards and are guaranteed for domestic use against manufacturing faults for a period of 12 months from the date of purchase. This warranty does not affect your statutory rights.

In case of any malfunction of your product (failure, missing parts, etc.) please contact us at our toll free service line at 1-866-518-0120 ext.262 from 9 am to 4 pm, Monday to Friday, Eastern Standard Time or by email at customerservice@simpli-home.com.

We reserve the right to repair or replace the defective product, at its discretion.

This product is guaranteed for 12 months if used for normal purposes. Any warranty is invalid if the product has been overloaded or subject to neglect, improper use or an attempted repair by other than an authorized agent. Heavy-duty or daily professional/commercial usage are not guaranteed.

Due to continuous product improvement, we reserve the right to change the product specifications without prior notice.