

FROGTAPE® 325 PINK PERFORMANCE GRADE HIGH TEMPERATURE, MEDIUM-HIGH ADHESION MASKING TAPE

TYPICAL APPLICATIONS

- For demanding, high temperature paint masking and metal fabrication applications in the transportation (auto, coaches, buses and marine) industry
- Also used for metal preparation, painting, coating and gel coat masking

PRODUCT FEATURES

- Excellent adhesion to metal, rubber, plastic, anodized aluminum, chrome and fiberglass
- Resistant to water, salt water, various solvents and abrasives
- Compatible with gel coats, multi-part epoxy topcoats, and antifouling bottom paints for marine applications, as well as solvent based and water-born, aqueous paints and coatings for automotive
- Resistant to water, various solvents and gel coats
- Residue-free removal
- Temperature-resistant up to 325 F (for up to 30 minutes)
- Remove tape at room temperature (70 F +/- 10 F) after baking

CONSTRUCTION

Backing: Fine Structured Crepe

Adhesive: Rubber-based adhesive

STANDARD WIDTHS

0.47 in; 0.70 in; 0.94 in; 1.41 in; 1.88 in; 2.83 in
12 mm; 18 mm; 24 mm; 36 mm; 48 mm; 72 mm

STANDARD LENGTH

60 yds

55 m

Lead times may apply. Please contact Shurtape customer service for information related to stock and non-stock sizes and colors.

STANDARD CORE SIZE

3 in

APPLICABLE STANDARDS

ASTM D 6123/D 6123M-97 (2012), Type I

AMS-T-21595

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

COLOR



PHYSICAL PROPERTIES

	STANDARD	METRIC
Adhesion to Stainless Steel	34 oz/in width	3.72 N/10 mm
Elongation	12%	12%
Service Temperature Range	40 F to 325 F (up to 30 minutes)	4 C to 163 C (up to 30 minutes)
Tensile	25 lbs/in width	43.8 N/10 mm
Thickness	6.4 mils	0.16 mm

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.



*DOES NOT contain PaintBlock® Technology.