




PROXIMITY CARD READERS ACCESS CONTROL

- CONDOMINIUM/RESIDENTS HALLS • GATED COMMUNITIES
- COMMERCIAL/INDUSTRIAL • MIXED USE • PARKING
- SELF STORAGE • MAXIMUM SECURITY



- Full line proximity card readers and cards
- Mullion, wall and post mount models
- Read ranges from 2- up to 30-inches (50.8mm to 76.2cm), and AVI long range adjustable from 8- up to 25-feet (2.4m to 7.6m)
- 5 year limited factory warranty



indoor use



outdoor use



post mount




cards & tags

ACCESS CONTROL SOLUTIONS


PROXIMITY CARD READERS ACCESS CONTROL

1815-305


9.38" W x 9.38" H x 1.38" D
238.3mm W x 238.3mm H x 35mm D
30-inch read range (762mm)




1815-300
Mullion



1815-301
Single Gang



1815-302
Small



1815-305

1815-300

1.81" W x 4.44" H
46mm W x 112.7mm H
3-inch read range (76.2mm)

1815-301

2.88" W x 4.44" H
73.2mm W x 112.7mm H
4-inch read range (101.6mm)

1815-302

1.69" W x 3.13" H
42.9mm W x 79.5mm H
2-inch read range (50.8mm)

Cards



1815-350

17.5" W x 17.5" H x 2.625" D
444.5mm W x 444.5mm H x 66.7mm D
25-foot read range (7.62m)



Technical Features

Proximity Cards / Key Tags

These cards will work with the following DK Prox readers only: 1815-300, 1815-301, 1815-302, 1815-330, 1815-331, 1815-305. Cards are sold in blocks of 50 only.

Cards

These cards are factory pre-coded. Card numbers may, or may not be, in numerical sequence.

- 1508-120 Clamshell Cards
- 1508-121 ISO Graphics Cards
- 1508-123 Key Tags

AVI Tags

- 1508-191 UHF Tag (works only with the 1815-350)
- 1508-198 UHF / DK Prox Dual Tag (works with AVI and DK Prox Readers)

- 1815-318 Windshield tag holder (optional)
- 1815-319 Rearview mirror holder (optional)

DKS Proximity Readers

- 1815-300; up to 3-inch read range
- 1815-301; up to 4-inch read range
- 1815-302; up to 2-inch read range
- 1815-305; up to 30-inch read range
- 1815-330; 1815-300 reader on a surface mount enclosure
- 1815-333; same as 1815-330 but also includes a Tracker expansion board.
- 1504-124; 1815-300 mounted on surface enclosure with built in intercom substation

AVI Long Range Reader

- 1815-350; 8- to 25-foot read range (adjustable). Includes reader control box.
- Frequency hopping technology.
- Operates in the UHF band (902-928 MHz).

Optional

- Surface / Gooseneck mount enclosure for the DKS 1815-305
- Include Tracker Board with the mount enclosure 1815-231

Electrical

PROXIMITY READERS	Input voltage / current
1815-300:	12 VDC – 200mA
1815-301:	12 VDC – 200mA
1815-302:	12 VDC – 200 mA
1815-305:	12 VDC Regulated - 2.0 A
2 color LED (Red, Green), Piezo Beeper	
Frequency: 125 kHz	
Output Format 26-bit wiegand	
AVI LONG RANGE READER	
1815-350:	12 VDC Regulated - 3.0 A
Frequency: 902-928 MHz	
Output Format 26-bit wiegand	



Operating Environment: -31°F to 149°F
(-35°C to 65°C)

Distributed by:



Access Control Solutions since 1948

MEMBER:



DOOR KING, INC.

120 Glasgow Avenue, Inglewood, California 90301 U.S.A.
Tel: 310-645-0023 FAX: 310-641-1586 www.doorking.com

© 2016 All Rights Reserved. Product specifications may change without notice.
Rev. 6/16