

CyberPower

P1208UC15BK

SURGE PROTECTOR

Protect home and office computers, and electronics.

The CyberPower P1208UC15BK Surge Protector provides essential surge protection for home and office electronics, including computers and other sensitive devices. Engineered to defend against power surges and energy spikes resulting from storms and electrical fluctuations, it offers 3000 joules of protection across twelve outlets. A durable 8-foot power cord ensures flexible placement, while the inclusion of one USB-A port and one USB-C port enables convenient charging of smartphones, tablets, and other mobile devices without occupying the primary outlets.

This surge protector comes with a One-Year Limited Warranty and a Connected Equipment Guarantee.

TYPICAL APPLICATIONS

- Mobile Devices
- Personal Electronics
- Cell Phones
- Personal Computers

FEATURES

- AC Outlets: 12
- Cord Length: 8-ft
- Surge suppression: 3000 J
- Plug type: NEMA 5-15P
- Plug style: Right angle, 45° offset
- Outlet type: NEMA 5-15R
- USB-A charge ports: 1
- USB-A charge output: 2.4A
- USB-C charge ports: 1
- USB-C charge output: 15W
- Volts: 125 V
- Warranty: One-Year Limited
- Connected Equipment Guarantee: \$300,000



SPECIFICATIONS

INPUT	
Cord Length	8 ft (2.4 m)
Input Plug Type	NEMA 5-15P
Maximum Input Current	15 A
Plug Style	Right Angle, 45° Offset

OUTPUT	
Outlet Type	12 x NEMA 5-15R
USB Charge Port Type	1 x Type A 1 x Type C
USB Charge Port Voltage	5 VDC
USB Charge Port Watts	18 Watts

# P1208UC15BK

## SURGE PROTECTOR

### SPECIFICATIONS CONT.

SURGE PROTECTION & FILTERING	
Clamping Voltage	800V (H-N, H-G, N-G)
Maximum Surge Current	75,000 A
Maximum Surge Current H-G	15,000 A
Maximum Surge Current H-N	45,000 A
Maximum Surge Current N-G	15,000 A
Surge Suppression (Joules)	3000 J
PHYSICAL	
Color	Black
Form Factor	Strip
Keyhole Mounting Slots	Yes
Material of Construction	Plastic
PHYSICAL DIMENSIONS	
Physical Dimensions - Width/Height/Depth (cm)	10.31 x 4.39 x 30.51 cm
Physical Dimensions - Width/Height/Depth (mm)	103 x 44 x 305 mm
Physical Dimensions - Width/Height/Depth (in.)	4.06 x 1.73 x 12.01 in.
Weight (kg)	0.83 kg
Weight (lb)	1.84 lbs.

SHIPPING DIMENSIONS	
Shipping Dimensions - Width/Height/Depth (cm)	17.81 x 36.3 x 5.0 cm
Shipping Dimensions - Width/Height/Depth (mm)	178.05 x 362.97 x 50.04 mm
Shipping Dimensions - Width/Height/Depth (in)	7.01 x 14.29 x 1.97 in.
Weight (kg)	0.94 kg
Weight (lb)	2.07 lbs.
CERTIFICATIONS	
Environmental	RoHS Compliant
Safety	cULus (UL1363/UL1449) DOE VI NR Can FCC ICES-003
WARRANTY	
CEG Amount	\$300,000
Connected Equipment Guarantee	Lifetime
Product Warranty	1-Year Limited Warranty