



Amplify[®] High Solids Floor Finish

Powered by FrescoMax Technology

A high solids UHS floor finish for floors that demand excellent gloss and durability

Features & Benefits

- Easy application and perfect leveling allows for easy installation with no mop drag
- Low odor finish ideal for 24-hour facilities
- Great mark resistance and durability
- Excellent reparability with spray buffing and burnishing

Applications

- For use on resilient and most hard surface flooring
- A sealer may be required for highly polished stone surfaces, glazed ceramic tile, luxury vinyl tile and some rubber floors
- Not intended for use on cork, wood, or bamboo flooring





Amplify[®] High Solids Floor Finish

Powered by FrescoMax Technology

Use Instructions

Preparation

- Always barricade area to be finished
- Before the first application of Amplify[®] High Solids Floor Finish, remove all old finish with recommended Diversey stripper

Coating

- Apply 3 or more medium coats of Amplify[®] High Solids Floor. Finish with a clean finish mop. Let dry to the touch between coats (about 30 minutes).
- On porous or stone floors, seal first with 2 coats of recommended Diversey sealer

Maintenance

- **Clean Daily:** Dust mop. Then wet clean with recommended Diversey cleaner in an autoscrubber or with a damp mop.
- Spray buff as needed with recommended Diversey spray buff, a red or beige pad and a 175–1500 RPM machine. Or burnish with a UHS pad and a battery, cord electric or propane machine at 1500–2000+ RPM.
- **Burnishing with Cleaner/Maintainer:** Clean and restore gloss with recommended Diversey Cleaner/Maintainer using an autoscrubber or damp mop, let floor dry and then burnish

Recoating

- Clean thoroughly. Dust mop. Machine scrub with a floor machine or autoscrubber using a blue pad and the recommended Diversey cleaner at the recommended dilution. Rinse well and let dry.
- Apply 2 new coats of Amplify[®] High Solids Floor Finish

Technical data	Amplify [®] High Solids Floor Finish
Color/Form	Opaque white, liquid
pH	8.2
Scent	Product specific
Shelf Life	2 Years

Product	Pack size	Dilution	Product code	
Amplify [®] High Solids Floor Finish	1 x 2.5 L / 2.64 qt. ProSpeed ^{TM/MC} BIB (Bag-in-Box)	Ready-to-use	4972034	
Amplify [®] High Solids Floor Finish	4 x 1 gal. / 3.78 L Containers	Ready-to-use	4385110	
Amplify [®] High Solids Floor Finish	1 x 5 gal. / 18.9 L Envirobox ^{TM/MC}	Ready-to-use	5104714	

Safe handling

Please make sure your employees read and understand the product label and Safety Data Sheet before using this product. The label contains directions for use; and both the label and SDS contain hazard warnings, precautionary statements and first aid procedures. SDS are available online at www.diversey.com or by calling 888.352.2249. Improper use or dilution may result in damage to surfaces and may result in health and physical hazards that match those of the concentrate. Please refer to the Diversey HazMat Library, only available through Internet Explorer, <http://naextranet.diversey.com/dot/>, for up-to-date shipping information.