



**MATERIAL**

PLASTIC HOUSING : ABS high-impact UL94V-0 thermoplastic  
INSERT:Stainless steel

**PHYSICAL CHARACTERISTICS**

OPERATING TEMPERATURE RANGE : -10 C TO 60 C  
STORAGE TEMPERATURE RANGE : -40 C TO 68 C  
HUMIDITY : 10%~90%RH

**ELECTRICAL**

IMPEDANCE: 75 ohm  
FREQUENCY RANGE: 0~2 GHz  
WORKING VOLTAGE: 250 VRMS max.  
DIELECTRIC WITHSTANDING VOLTAGE: 500VRMS min.  
VSWR: 1.35 max  
CONTACT RESISTANCE: 1.Center Contact: 5 Milliohms Max.  
2.Outer Contact: 1 Milliohms Max.  
INSULATOR RESISTANCE: 1000 Megohms min.

Colors Available: White

|                      |            |  |      |       |                 |
|----------------------|------------|--|------|-------|-----------------|
| Scale                | 1.5:1      | All Copy Rights Reserved                       |      |       |                 |
| 3rd Angle Projection |            | BNC KEYSTONE SNAP-IN INSERT- NICKLE-PLATED, UL |      |       |                 |
| Unit                 | mm         | SCP P/N<br><b>208-XX</b>                       |      |       |                 |
| Date                 | 2015-09-16 |  |      |       |                 |
| Tolerance            |            |  |      |       | Drawn by<br>FHL |
| ~20                  | ~50        | ~150   | 150~ | ANGLE |                 |
| ±0.2                 | ±0.4       | ±0.5   | ±1.5 | ±2°   |                 |