

B603RC1 ESSENTIAL SURGE PROTECTOR

Protect home and office computers, electronics, and home theater equipment

The Essential Surge Protector B603RC1 offers vital surge protection for common home and office devices such as chargers and small electronics. It prevents spikes in energy caused by storms and electrical power surges from reaching your electronic equipment. The B603RC1 provides 600 joules of protection with 6 outlets and a power cord (3 ft.).

Features of the B603RC1 include an On/Off switch with integrated 15-Amp circuit breaker (resettable), EMI/RFI noise filter, metal oxide varistor (MOV) technology, keyhole mounting slots (back), and damage-resistant construction. This surge suppressor comes with a Limited Lifetime Warranty and a \$25,000 Connected Equipment Guarantee.

TYPICAL APPLICATIONS

- Personal Computers
- Chargers
- Personal Electronics

FEATURES

- Surge suppression: 600 J
- Volts: 125 V
- Circuit breaker: 15 A
- Outlet type: 6 surge-protected
- Power cord: 3 ft
- Color: Black
- EMI/RFI Filtration: Yes
- Warranty: Limited Lifetime
- Connected Equipment Guarantee: \$25,000



SPECIFICATIONS

INPUT		SURGE PROTECTION & FILTERING - CONT.	
Circuit Breaker	15 A	Maximum Surge Current	30,000 A
Cord Length	3 ft (0.9 m)	Maximum Surge Current H-G	10,000 A
Input Plug Type	NEMA 5-15P	Maximum Surge Current H-N	10,000 A
Maximum Input Current	15 A	Maximum Surge Current N-G	10,000 A
Nominal Input Voltage	125 VAC	Maximum Surge Voltage	6,000 V
Plug Style	Straight	Response Time	<1 Nanosecond
OUTPUT		SURGE PROTECTION & FILTERING - CONT.	
Outlet Type	6 NEMA 5-15R	Surge Suppression (Joules)	600 J
Outlets - Total	6	PHYSICAL	
SURGE PROTECTION & FILTERING		Color	Black
Clamping Voltage	400V (H-N, H-G, N-G)	Form Factors Supported	Keyhole (Wall Mount or Under-counter Installation)
EMI/RFI Filtration	150 KHz 100 MHz Yes	Keyhole Mounting Slots	Yes
		Material of Construction	Plastic

B603RC1

ESSENTIAL SURGE PROTECTOR

SPECIFICATIONS CONT.

DIMENSIONS		CERTIFICATIONS			
Physical Dimensions - WxHxD (cm)	4.45 x 3.78 x 26.04 cm	Environmental	RoHS Compliant		
Physical Dimensions - WxHxD (mm)	44 x 38 x 260 mm	Safety	cUL		
Physical Dimensions - WxHxD (in.)	1.75 x 1.49 x 10.25 in.	WARRANTY			
Weight (kg)					
Weight (lb)					
SHIPPING DIMENSIONS		CEG Amount	\$25,000		
Shipping Dimensions - WxHxD (cm)	3.89 x 29.21 x 8.03 cm	Connected Equipment Guarantee	Lifetime		
Shipping Dimensions - WxHxD (mm)	38.86 x 292.1 x 80.26 mm	Product Warranty	Limited Lifetime Warranty		
Shipping Dimensions - WxHxD (in.)	1.53 x 11.5 x 3.16 in.				
Shipping Weight (kg)	5.35 kg				
Shipping Weight (lbs.)	11.8 lbs.				