

# EV 97

**Shurtape®**  
TRUE TO YOUR WORK™

## PREMIUM GRADE, UL LISTED BLACK ELECTRICAL TAPE

### TYPICAL APPLICATIONS

- For primary insulation of electrical splices up to 600 V
- Also used as a jacketing on high voltage splices and repairs
- Can be used when wrapping wire harnesses and cables
- For indoor and outdoor use

### PRODUCT FEATURES

- All-weather performance
- Highly conformable
- High tensile strength
- Hand-tearable
- Lead free
- Flame retardant
- High performance in a wide temperature range
- Resistant to UV, oils, acids, alkalis, corrosive chemicals and water

### CONSTRUCTION

Overall Grade/Function: Premium  
Backing: Polymeric polyvinylchloride (PVC)  
Adhesive: Non-corrosive, rubber-based

### STANDARD WIDTH(S)

¾ in 19 mm

### STANDARD LENGTH(S)

66 ft 20 m

Contact your Shurtape sales representative for other available sizes

### APPLICABLE STANDARDS

UL Listed; CSA 22.2

### STORAGE AND USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

### COLOR(S)



### PHYSICAL PROPERTIES STANDARD METRIC

Tensile Strength	26 lbs/in width	45.5 N/10 mm
Adhesion to Stainless Steel	28 oz/in width	3.06 N/10 mm
Thickness	8.5 mils	0.216 mm
Elongation	300%	300%
Dielectric Strength	1,294 V/mil	1,294 V/mil
Dielectric Breakdown	11,000 V	11,000 V
Service Temperature Range	0 F to 220 F	-18 C to 105 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

