



REVISIONS	
ISSUE	CHANGES
0	ER 8307 MS 18 FEB 70
1	CN 8306 A L.R. 6/7 MAR. 70
2	FORMAT CN 10986C J.G.L. 7 APR 72
3	CN 11247A C.C. 20 JUN 72
4	CN 24956 C M.A. 18 ALL 83

1702-1

NOTES:

1. FOR USE WITH RG-59, 62 & 2101U CABLE.
2. FOR CABLING INSTRUCTIONS SEE CP-441.
3. FOR CABLE TRIMMING USE KTJ-72 AND KTD-134.
4. FOR CRIMPING USE DIE SIZE 42.
5. ITEM ① TO HAVE M27 (RUBERIZE) AFTER PATING.

S.D

QTY	REQ'D	DESCRIPTION	DRAWING NO.
8	1	SHV CRIMP CONTACT M	1-3/2-3-M29
7	1	HEX. NUT	492A-9-M06
6	1	RETAINING RING	
5	1	LOCKWASHER	492A-12-M06
4	1	GASKET	492A-10-M99
3	1	INSULATOR	
2	1	BODY	
1	1	W/P KGRIP SLEEVE (SEE NOTES)	C-59-228-5-M06

REF:	
FINISH	
SPEC. KER-10004	
MATEL	
SPEC.	
SHV BULKHEAD JACK	
DRAWN R. D.	DATE 19 AUG. 69
APPR. MS	DATE 18 FEB 70
KINGS ELECTRONICS 40 WARSLEDALE ROAD TUCKAHOE, N. Y. 10707	
1702-1	

UNLESS OTHERWISE SPECIFIED:

1. TOLERANCES: FRACTIONS & 2 PLACE DECIMALS ± .010
3 PLACE DECIMALS ± .004 ANGLES ± 0° 30'
2. REMOVE ALL BURRS, BREAK SHARP EDGES .005 MAX.
3. NO FILLETS PERMITTED.
4. SURFACE ROUGHNESS 63 MICROINCHES RMS MAX.
5. ALL DIMENSIONS PRIOR TO PLATING.