

Jones Stephens' PlumBite® Push to Connect Water Heater Connector With Ball Valve

Job Name	_____
Location	_____
Engineer	_____
Contractor	_____
Tag	_____ PO# _____

Specifications

Jones Stephens' PlumBite® Push to Connect Water Heater Connectors With Ball Valves are a heat-free method of joining Copper, CPVC, PE-RT or PEX tubing, designed to save time on installation and to connect piping with relative ease and confidence. No soldering, glue, heat or external tools are required to join the pipe. Just insert the pipe and the stainless steel gripper ring, bite down, and hold the pipe tightly while the EPDM o-ring seals against leakage. Disassembly is just as fast using the optional disassembly tool, so fittings can be easily removed and re-used.

Applications

Jones Stephens' PlumBite® Push to Connect Water Heater Connectors With Ball Valves are approved for use with commercial and residential potable and non-potable water applications.

Materials

Gasket- EPDM, Peroxide Cured
Valve Body- Brass

Dimensions and Product Offering

PART NO.	A NOMINAL (IN.)	B NOMINAL (IN.)	C (IN.)	C TOLERANCE +/- (IN.)
C77477LF	0.75 FIP	0.75	18.55	0.40
C76616LF	0.75 FIP	0.50	18.55	0.40
C76617LF	0.75 FIP	0.75"	18.55	0.40

Performance Specifications

Maximum Temperature - 180°F
Maximum Pressure - 200 PSI

Certifications/Listings/Approvals

- NSF/ANSI/CAN 61
- NSF/ANSI/CAN 372
- ASME A112.18.6/CSA B125.6
- SDWA Compliant
- Lead Law Compliant
- MASS Approved

