

91031, 91032, 91033, 91034 INSTALLATION INSTRUCTIONS

Please read carefully and save these instructions as you may need them a later date.

CAUTION

WARNING: Risk of Fire. Consult a qualified electrician to ensure correct branch circuit conductor.

Turn off the main power at the circuit breaker before installing the fixture in order to prevent possible shock.

GENERAL

All electrical connections must be in accordance with local and National Electrical Code (N.E.C.) standards. If you are unfamiliar with proper electrical wiring connections obtain the services of a qualified electrician.

Remove the fixture and the mounting package from the box and make sure that all parts are missing by referencing the illustration.

ASSEMBLY AND INSTALLATION

1. Secure the mounting plate(3) to the outlet box(6) with the outlet box screws(1).
2. Pull out the wires and ground wire from the outlet box(6).
Make wire connections with Wire caps(4):
 - Connect White wire(5) from the fixture to the white wire from the power source.
 - Connect Black wire(7) from the fixture to the black wire from the power source.
 - Attach the fixture ground wire to mounting plate(3) with the ground screw(8). Connect it to the house ground wire with the wire cap(4).
3. Carefully tuck the connected wires back into the outlet box(6).
3. Align the backplate(10) to the outlet box(6), then secure it to the mounting plate(3) with the finials(11).
4. Unscrew the socket rings(15) from sockets(13). Set glass shades(14) and secure them with socket rings(15) tightly.
5. Install bulbs: (bulbs not included)
(Don't exceed the maximum capacity recommended on the Sockets).

INSTALLATION IS NOW COMPLETED

