



A superior tinted water-based sealant formulation that provides long lasting wood protection. It is formulated to minimize odor and has 0 VOCs. Onex-Seal II is a unique, penetrating sealant that adds water repellency to wood surfaces to help prevent water damage.

## Features & Benefits

- Zero VOC
- Fast Drying
- No Offensive Solvent Odor
- Designed for interior use

## Item Number & Unit of Measure

Item Number	HIL0031506
Unit of Measure	1 gal Bottle

## Specifications

Color	Brown
Appearance	Translucence
Fragrance	Non-Objectionable
Formula Type	Liquid
Dilution Ratio	RTU
PH	N/A
Coverage SqFt/Gallon	300
Dry Time (hrs.)	24 hrs
Sheen	Matte

UL Certified	Yes
--------------	-----

## Safety

See safety datasheet (if applicable) and product label for safety information, handling and proper use.

## Directions for Use

**DIRECTIONS FOR USE:** ONEX-SEAL II should be stirred before start of application for 15 minutes for best results. Apply ONEX-SEAL II to hardwood flooring at a rate of 300 square feet per gallon with hand sprayer or recommended applicators below.**RECOMMENDED APPLICATORS:** Brush or lambswool applicator.**HAZARD STATEMENT:** This mixture does not meet the criteria for classification.**PRECAUTIONARY STATEMENTS: Prevention:** Observe good industrial hygiene practices.**RESPONSE:** Wash hands after handling.**STORAGE:** Store away from incompatible materials.**DISPOSAL:** Buyer assumes all risk and liability associated with disposal of this product (original concentration or dilution) in violation of applicable law in compliance with applicable federal, state and local requirements.**CONTAINER DISPOSAL:** Triple rinse (or equivalent). Then offer clean, dry container for recycling or reconditioning.**NOTE:** Use with adequate ventilation. Do not aerosolize or mist the product. If spray is used, use a coarse spray. Avoid breathing/mist/vapors/spray.**DISCLAIMER OF WARRANTY** SELLER MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, EXCEPT THAT THIS PRODUCT SHALL BE OF SELLER'S STANDARD QUALITY.