



CRC Industries NZ
Auckland NZ

I. Product Description

CRC Food Grade Machine Oil is a highly refined machine oil engineered to provide exceptional lubrication characteristics and high levels of wear and corrosion protection. For use in circulation systems lubricating gears and bearings on all food processing equipment.

Temperature range from -20°C to +150°C (continuous), +170°C (intermittent). MPI Approved C15. NZ AsureQuality assessment for food/beverage including dairy factories with incidental contact. NSF H1 Registered for incidental food contact. Meets FDA Regulations 21 CFR 172.878; 21 CFR 178.3620; and 21 CFR 573.680 for incidental food contact.

II. Features & Benefits

- **Excellent wear protection** – Improved gear and bearing performance
- **Ongoing protection against corrosion**
- **Non silicone** – Will not harm paint, plastic or wood surfaces. Easier clean-up and removal of excess oil. Allows treated surfaces to be repainted
- **High Flash Point** – Provides increased user safety
- **360°C degree valve** – Aerosol can be sprayed from any position even upside down
- **Non-toxic, colourless, odourless, tasteless**
- **Temperature Range** – Effective from -20°C to +150°C (continuous), +170°C (intermittent)
- **MPI Approved C15**
- **NZ AsureQuality assessment for food/beverage including dairy factories with incidental contact**
- **NSF H1 Registered for incidental food contact**
- **Meets FDA Regulations 21 CFR 172.878; 21 CFR 178.3620; and 21 CFR 573.680 for incidental food contact**

III. Application and Directions

Preparation:

1. Do not use on energized systems.

Application:

1. Hold can 200mm to 300mm away from surface to be sprayed.
2. Spray a light, even film on area to be lubricated.
3. Wipe off excess with cloth.
4. Repeat application when necessary

IV. Typical Properties and Characteristics

Physical Properties:

| | |
|------------------|-------------------|
| Flash Point | >190°C (TCC) |
| Boiling Point | +215°C Initial |
| Odour | None |
| Appearance | Colourless liquid |
| Vapor Density | > air |
| Solubility | Neg. in water |
| % Volatile | 65% |
| Specific Gravity | 0.815 |
| Viscosity | 38-41 cST @ 40°C |
| Propellant | Carbon Dioxide |



CRC Industries NZ
Auckland NZ

Technical Data Sheet – 3092

CRC Food Grade Machine Oil

Performance Characteristics:

| | |
|-------------------|---|
| Type of film | Thin, oily film |
| Dry Time | Non-drying wet oil |
| Temperature Range | -20°C to +150°C (continuous), +170°C (intermittent) |

V. Package Description

| Part Number | Size |
|-------------|--------------|
| 3092 | 312g Aerosol |

VI. Special Precautions

General:

Use with adequate ventilation. Store in a cool, well-ventilated area. Dispose of empty containers safely. All unused product should be disposed of in conformance with local and HSNO regulations, do not contaminate water supply.

Aerosol Cans:

Do not puncture, incinerate or store above 50°C. Exposure to high temperatures may cause can to burst. Do not place in direct sunlight or near any heat source. Aerosol cans will conduct electricity. Keep away from all live electrical sources including battery terminals, solenoids, electrical panels and other electronic components. Failure to observe this warning may result in serious injury from flash fire and/or electrical shock.

First Aid:

Swallowed – Not considered a normal route of entry.

Skin – Remove contaminated clothing and wash skin thoroughly with soap and water. Remove any adhering solids with industrial skin cleansing cream. Do not use solvents. Seek medical attention in the event of irritation. Wash contaminated clothing before reuse.

Eyes – Immediately hold the eyelids apart and flush the eye continuously for at least 15 minutes with fresh running water.

Inhaled – Remove to fresh air. Lay patient down. Keep warm and rested.

Refer to Material Safety Data Sheet for more details.

TECHNICAL DATA SHEET Version 05/2015

PRODUCT WARRANTY: CRC offers a conditional warranty of this product for the period of 2 years from the date of manufacture.

DISCLAIMER: All information on this data sheet is based on testing by CRC Industries NZ. All products should be tested for suitability on a particular application prior to actual use. CRC Industries makes no representations or warranties of any kind concerning this data.