

How the best get better.




than 3M[™] Cubitron[™] II Fibre Discs 982C

Introducing 3M[™] Cubitron[™] II Fibre Disc 982CX Pro

featuring re-engineered 3M Precision-Shaped Grain and redesigned construction.







Specialty Vehicle

Applications:

Weld Removal

ndustries:

Beveling


Machinery Manufacturing

Transportation

- Grinding
- Scale Removal
- Heavy Deburring

Use On:

Carbon Steel



Contaminant-free and INOX compliant

3M[™] Cubitron[™] II Fibre Disc 982CX Pro

The new 3M[™] Cubitron[™] II Fibre Disc 982CX Pro features reinvented precision-shaped grain and redesigned construction for longer life and improved performance.

- Faster cutting and longer lasting than our legendary 3M[™] Cubitron[™] II Fibre Discs 982C
- Cuts with less pressure—designed to help reduce operator fatigue
- Ideal for medium and high-pressure applications like weld removal, beveling and other aggressive grinding applications
- Use on carbon steel

3M[™] Disc Back-up Pad, Ribbed-Extra Hard

These new back-up pads provide the firm support required for grinding applications. They feature a convenient, one-piece design for quick and easy assembly. The extra hard, stiff density of this back-up pad helps optimize the life and performance of 3M[™] Cubitron[™] Fibre Discs 982CX Pro and other coarse grade 3M[™] Fibre Discs.




TECH TIP:

For best results, 3M recommends using the 3M[™] Disc Back-up Pad, Ribbed-Extra Hard with 3M[™] Cubitron[™] Fibre Discs 982CX Pro. It will help provide a consistent cut and optimize abrasive life and performance.


3M Precision-Shaped Grain re-engineered.

Conventional ceramic abrasive grain tends to "plow" through metal, causing heat to build up in the workpiece and the abrasive, resulting in a slower cut and shorter abrasive life.




Conventional Ceramic Abrasive

3M pioneered the first precision-shaped grain using 3M microreplication technology to form consistent sharp peaks that easily "slice" through metal—cutting cooler, faster and lasting longer than conventional abrasive grain.




3M Precision-Shaped Grain

And now, we've done it again.



The first time you use 3M[™] Cubitron[™] II Discs 982CX Pro with the newly re-engineered, precision-shaped grains, you'll instantly notice the difference. We've taken the legendary cutting speed and life of 3M[™] Cubitron[™] II abrasives to a new level—outperforming our original precision-shaped grain.



*Results based on an automated, 11 minute test on 1018 steel using 3M[™] Cubitron[™] II Discs 982CX Pro, 7 inch disc and 3M[™] Disc Pad Face Plate Ribbed 80514 on a servo motor.

Product Information

Product	UPC	Diameter (Inches)	Max RPM	Min/Case
3M [™] Cubitron [™] II Fibre D	isc 982CX Pro, Grade 36+			
	06-38060-83330-8	4 × 5⁄8	15,000	25/100
	06-38060-83328-5	4 × 1/8	15,000	25/100
	06-38060-83313-1	4 ½ x %	13,300	25/100
	06-38060-83314-8	5 × %	12,000	25/100
	06-38060-83327-8	6 × %	10,000	25/100
	06-38060-83315-5	7 × %	8,600	25/100
	06-38060-83316-2	9 ½ × ½	6,600	25/100
TN Quick Change				
Ø	06-38060-83320-9	4 ½ x 5⁄8-11	13,300	25/100
	06-38060-83317-9	5×⁵⁄₃-11	12,000	25/100
	06-38060-83331-5	7 × 5⁄8-11	8,600	25/100
GL Quick Change				
0	06-38060-83329-2	4 ½ x 5⁄8-11	13,300	25/100
	06-38060-83318-6	5×⁵⁄₃-11	12,000	25/100
	06-38060-83319-3	7 × 5⁄8-11	8,600	25/100
3M [™] Disc Back-up Pad, R	ibbed, Extra Hard – one-piece			
	06-038060-88655-7	4 1/2	13,300	10
	06-038060-88656-4	5	12,000	10
	06-038060-88657-1	7	8,600	10
3M [™] Disc Back-up Pad M	ounting Kit (not required for use wit	h 3M [™] Pneumatic Angle Gr	inder or Sander)	
000	06-38060-88968-8	Includes 3M [™] Retainer Nut PN 02618, ¾6″ PG Wheel Spacer and ½″ Spacer.		1

3M[™] Disc Back-up Pad and Mounting Kit are both sold separately

Take advantage of performance and productivity that will set your shop up for success. **3M.com/Metalworking**

Warranty and Limited Remedy: 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER EXPRESS OR IMPLIED WARRANTIES OR CONDITIONS, INCLUDING ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. If a 3M product does not conform to this warranty, the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price. Limitation of Liability: Except for the limited remedy above, and except to the extent prohibited by law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential, regardless of the legal or equitable theory asserted.



Abrasive Systems Division 3M Center, Building 233-6N-02 St. Paul, MN 55144-1000 1-866-279-1235 3M.com/Metalworking