



# PR3000RTXL2UTAA

## SMART APP

## SINEWAVE UPS

Protect corporate and network servers, telecom installations, and VoIP systems.



The PR3000RTXL2UTAA is a Smart App Sinewave rack/tower convertible UPS with line-interactive topology, surge protection, and battery backup. CyberPower's Smart App Sinewave series has sine wave output to eliminate power gaps that can be detected by sensitive equipment and cause unexpected shutdowns.

The Smart App Sinewave PR3000RTXL2UTAA improves battery life through battery equalization technology and Automatic Voltage Regulation (AVR), which corrects minor power fluctuations without switching to battery power. The new chassis design with an easy-to-access toolless front panel, color-coded rear panel, and captive screws for battery panel access make installations and battery changes simple and fast. The PR3000RTXL2UTAA also has a new LCD panel that rotates 90°, tilts for a better viewing angle, and provides information on 47 different settings including UPS stats, UPS setup and control management, and testing options.

### TYPICAL APPLICATIONS

- Servers
- Workstations
- Network Devices
- Telecom Equipment

### FEATURES

- 3000VA/3000W
- Line-Interactive Topology
- GreenPower UPS™
- 2U Rack Mount/Tower Convertible

## SPECIFICATIONS

GENERAL		OUTPUT	
UPS Topology	Line-Interactive	VA	3000
Energy Saving	GreenPower UPS™ Bypass Technology	Watts	3000
ENERGY STAR® Certified	Yes	Automatic Voltage Regulation	Double Boost, Single Buck
Active PFC Compatible	Yes	On Battery Voltage	100/110/120Vac ± 5%
INPUT		On Battery Frequency	50/60 Hz ± 1%
Voltage	100 - 120 VAC	On Battery Waveform	Sine Wave
Frequency	47 - 63 Hz	Outlets - Total	9
Input Voltage Range	75 - 149 VAC	Outlet Type	8 x NEMA 5-20R; 1 x NEMA L5-30R
Plug Type	NEMA L5-30P	Outlets - Critical Load	4
Plug Style	Straight, Twist Lock	Outlets - Battery & Surge Protected	9
Cord Length	10 ft.		

# PR3000RTXL2UTAA

## SMART APP SINEWAVE UPS



### SPECIFICATIONS CONT.

OUTPUT CONT.		MANAGEMENT & COMMUNICATIONS	
Rated Power Factor	1	LED Indicators	Power On, Line Mode, Battery Mode, Fault, Night Mode, Wiring Fault
Overload Protection	Internal Circuitry Limiting/ Circuit Breaker	Audible Alarms	Battery Mode, Low Battery, Overload, Overcharge, Overheat
Transfer Time	4 ms typical	Software	PowerPanel® Business
BATTERY			SNMP/HTTP Remote Monitoring
Runtime at Half Load (min)	1.7		Yes - With Optional RMCARD205TAA
Runtime at Full Load (min)	7	PHYSICAL	
Battery Type	Sealed Lead-Acid	Rack Size	2U
Battery Size	12V / 9AH	Form Factor	Rack/Tower
Hot-Swappable	Yes	Dimensions (WxHxD) (in.)	17.1 x 3.4 x 19.7
Replacement Battery	RB1290X4J	Weight (lbs.)	75.4
Battery Quantity	4	Shipping Dimensions (WxHxD) (in.)	22.1 x 10.8 x 24.4
User Replaceable	Yes	Shipping Weight (lbs.)	89.5
Typical Recharge Time	3 hrs	ENVIRONMENTAL	
External Battery Pack Option	BP48VP2U02TAA	Operating Temperature	32°F to 104°F (0°C to 40°C)
SURGE PROTECTION & FILTERING			Operating Relative Humidity
Network Protection RJ45	1 - In, 1 - Out	Storage Temperature	5°F to 113°F (-15°C to 45°C)
Surge Suppression	2,430 Joules	Maximum Operating Elevation	10,000 ft (3,000 m)
EMI/RFI Filtration	Yes	Maximum Storage Elevation	50,000 ft (15,000 m)
MANAGEMENT & COMMUNICATIONS			AC Mode Thermal Dissipation
Multifunction LCD Panel	47 Settings (27 Setup and Control Items + 20 Status Updates and Log Menus)		120.8 BTU/hr
HID Compliant USB Port	Yes	CERTIFICATIONS	
Serial Port	Yes	Safety	UL1778, cUL1071, FCC Class A
EPO Port	Yes	Environmental	RoHS Compliant
Contact Closure	Yes	WARRANTY	
Management Cable	USB Cable, EPO Cable	Product Warranty	Three-Years Limited
		Connected Equipment Guarantee	Lifetime
		CEG Amount	\$400,000