

## FEATURES & SPECIFICATIONS

### INTENDED USE

For use with housings L3 and L3R.

### CONSTRUCTION

Aluminum one piece reflector. Deep black has white flange as standard.

Polyester powder coat paint.

### INSTALLATION

Socket to trim interface.

Retaining clips pull and snap onto top of reflector to hold trim inside housing.

### LISTINGS

UL Listed to US and Canadian safety standards.

Damp location listed.

Pull on clip Patent No. (US) 5707143, (Canada) 2193902.

### WARRANTY

1-year limited warranty. Complete warranty terms located at [www.acuitybrands.com/CustomerResources/Terms\\_and\\_conditions.aspx](http://www.acuitybrands.com/CustomerResources/Terms_and_conditions.aspx)

Actual performance may differ as a result of end-user environment and application.


Note: Specifications subject to change without notice.

Catalog Number
Notes
Type

4" Finishing Trim

# 3B2

**BAFFLE DEEP**  
Narrow Flange




### Specifications

Height: 5-1/4" (13.3)

Lamp opening: 3-1/2" (8.9)

Diameter: 4-7/8" (12.4)

All dimensions are inches (centimeters) unless otherwise indicated.



### ORDERING INFORMATION

All configurations of this product are considered "standard" and have short lead times.

**Example: 3B2**

3B2	
Series	Finish
3B2	(blank) Black baffle W White baffle

Housing Compatibility: Housing and trim ordered separately.			
Application	Source	Maximum wattage	Housing
IC	Incandescent	35 PAR20 <sup>1</sup>	L3, L3R
		30 R20 <sup>1</sup>	
Non-IC	Incandescent	50 PAR20 <sup>1</sup>	L3, L3R
		50 R20	

### Notes

1 White baffle (3B2W) only.

