



CSP806TTAA Professional Surge Protector

Offering home/office environments with computer and communication grade surge protection.

The CyberPower Federal Trade Agreements Act (TAA) compliant CSP806TTAA Surge Protector is ideal for Home/Office protection with 2550 joules, 8 outlets, RJ11 (1 in / 2 out) phone line protection, and a 6 ft. cord. The surge protector is ideal for protecting personal computers, phones/fax/modems, printers, stereos, and consumer electronics.

The CSP806TTAA features eight (8) outlets with four (4) widely spaced outlets to accommodate transform sized plugs, MOV technology to guard the surge protector and connected electronics against line abnormalities and lightning surges, while EMI/RFI filters block unwanted line noise. Data line protection is provided for telecommunication devices such as phones, faxes, modems, and DSL lines.

A Limited Lifetime Warranty ensures that this surge protector has passed our highest quality standards in design, assembly, material or workmanship and further protection is offered by a \$250,000 Connected Equipment Guarantee.

Typical Applications

- Desktop Computers
- Routers & Modems
- Personal Electronics

Features

- 8 Surge Protected Outlets
- 2550 Joules of Surge Protection
- DSL / Phone / Fax Protection - RJ11
- 15A Circuit Breaker
- 6 ft. Cord
- EMI/RFI Noise Filters
- Lifetime Warranty

CSP806TTAA Professional Surge Protector

Offering home/office environments with computer and communication grade surge protection.

GENERAL	
Product Type	Surge Protector
INPUT	
Voltage	125V
Rotating Power Cord	None
Switch	Non Lighted On/Off - Reset
Circuit Breaker	15 Amp
Plug Type	NEMA 5-15P
Plug Style	Right Angle - 45° Offset
Cord Length	6'
OUTPUT	
Outlets - Total	8
Outlet Type	NEMA 5-15R
Outlets - Energy Saving	0
Outlets - Widely Spaced	4
SURGE PROTECTION & FILTERING	
Surge Suppression	2,550 Joules
Maximum Surge Current	120,000 Amps
Maximum Surge Current H-N	60,000 Amps
Maximum Surge Current H-G	30,000 Amps
Maximum Surge Current N-G	30,000 Amps
Clamping Voltage	400V (L-N, L-G, N-G)
Response Time	< 1 nanosecond
Phone Protection RJ11	1-In, 2-Out
EMI/RFI Filtration	150 kHz to 100 MHz
Attenuation	Up to 43dB
INDICATORS	
Indicators	Protected (Green), Grounded (Green)
PHYSICAL	
Keyhole Mounting Slots	Yes
Cord Management	Yes
Safety Covers	Yes
CERTIFICATIONS	
Safety	UL1363 / UL1449 3rd Edition, cUL
Environmental	RoHS Compliant
WARRANTY	
Product Warranty	Limited Lifetime
Connected Equipment Guarantee	Lifetime
CEG Amount	\$250,000