



# MP1095WS2PK MULTI-PACK SOLUTION

Power, surge protection, and USB charging solutions for home and office electronics

The CyberPower MP1095WS2PK combo pack comes with two 8-outlet surge protector strips with USB-A and USB-C and two 6-outlet wall-tap surge protectors with USB-A and USB-C.

The 8-outlet surge protectors in this combo pack each provide 2700 joules of protection to prevent damaging power spikes and surges from reaching your electronics. They feature 2 USB ports (one 2.4A USB-A port and one 15W USB-C port) that will charge USB-enabled mobile devices and small electronics. The P806UC36A models each have a 6-foot power cord, a low-profile plug that fits in tight spaces, LEDs that indicate protected and grounded status, and a One-Year Limited Warranty.

The 6-outlet surge protector wall-taps in this combo pack provide 2000 joules of protection to prevent damaging power spikes and surges from reaching your electronics. They each feature 2 USB ports (one 2.4A USB-A port and one 15W USB-C port) that will charge USB-enabled mobile devices and small electronics. The P6WSUC has swiveling outlets that rotate 90 degrees to help with cord management, LEDs that indicate protected and grounded status, and a One-Year Limited Warranty.



## TYPICAL APPLICATIONS

- Personal Computers
- Chargers
- Personal Electronics

## FEATURES — SURGE PROTECTOR WALL-TAPS WITH USB

- AC outlets: 6
- Outlet type: NEMA 5-15R
- Surge suppression: 2000J
- USB-A ports: 1
- USB-A output: 2.4A
- USB-C ports: 1
- USB-C output: 15W
- Plug type: NEMA 5-15P
- Warranty: One-Year Limited

## FEATURES — SURGE PROTECTOR POWER STRIPS WITH USB

- AC outlets: 8
- Outlet type: NEMA 5-15R
- Surge suppression: 2700J
- USB-A ports: 1
- USB-A output: 2.4A
- USB-C ports: 1
- USB-C output: 15W
- Plug type: NEMA 5-15P
- Plug style: Right-angle 45° offset
- Power cord length: 6 ft.
- Warranty: One-Year Limited

MP1095WS2PK

MULTI-PACK SOLUTION

SPECIFICATIONS

	P806UC36A POWER STRIPS	P6WSUC WALL-TAPS
INPUT		
Voltage	125V	
Plug Type	NEMA 5-15P	
Plug Style	Right Angle, 45° Offset Right	Three Prong Direct Plug-in
Cord Length	6 ft	Wall-tap
OUTPUT		
Outlet Type	NEMA 5-15R	
Outlets - Total	8	6
Output Voltage	125V	
USB Charge Ports	1 USB-A, 1 USB-C	
USB-A Charge Port Output	5V / 2.4A	
USB-C Charge Port Output	5V / 15W	
SURGE PROTECTION & FILTERING		
Attenuation	32 dB	
Surge Suppression	2700J	2000J
Clamping Voltage	600 V (L-N, L-G, N-G)	
Response Time	< 1 Nanosecond	
EMI/RFI Filtration	150 KHz to 100 MHz	
INDICATORS		
LED Indicators	Protected (green) Grounded (green)	
PHYSICAL		
Color	White	
Keyhole Mounting Slots	No	

	P806UC36A POWER STRIPS	P6WSUC WALL-TAPS
DIMENSIONS		
Product Dimensions (WxHxD) cm	9.91 cm x 3.1 cm x 19.81 cm	10.31 cm x 16.23 cm x 5.54 cm
Product Dimensions (WxHxD) mm	99 mm x 31 mm x 198 mm	103 mm x 162 mm x 55 mm
Product Dimensions (WxHxD) in	3.9 in. x 1.22 in. x 7.8 in.	4.06 in. x 6.39 in. x 2.18 in
Shipping Dimensions (WxHxD) cm	18 cm x 36.5 cm x 6 cm	
Shipping Dimensions (WxHxD) mm	180 mm x 365 mm x 60 mm	
Shipping Dimensions (WxHxD) in	7.09 in. x 14.37 in. x 2.36 in.	
Shipping Weight (kg)	1.09 kg	
Shipping Weight (lbs.)	2.40 lbs.	
CERTIFICATIONS		
Environmental	RoHS Compliant	
Safety	UL1363, 1449, 1310, cUL, FCC, DOE VI, CEC/ IC, NRCan	UL498A, 1449, 1310, cUL, FCC, DOE VI, CEC/ IC, NRCan
WARRANTY		
Product Warranty	One-Year Limited Warranty	
Connected Equipment Guarantee	Yes	
CEG Amount	\$100,000	