

# Iron Stone®

## **Acrylic Seal**

Iron Stone® Acrylic Seal is for use on resilient and stone surfaces with excellent leveling and adhesive characteristics, even on worn surfaces.

#### Features & Benefits

- Provides superior compatibility for a wide range of resilient and stone surfaces
- Protects against soil penetration and staining
- Easy to apply and strips easily with any Diversey stripper

### **Applications**

• For use as a sealer on any stone, resilient and porous surface





# Iron Stone®

**Acrylic Seal** 

#### **Use Instructions**

- Do not dilute (when applicable)
- Do not use on surfaces colder than 50° F (10° C)
- To avoid contamination, do not return unused product to original container

**Note:** Floors will be slippery when wet or contaminated with foreign materials. Promptly clean-up spills and foreign materials. Meets ASTM D-2047 requirement for slip resistance.

#### Preparation

- Blockade areas to be stripped, sealed or finished. Floors will be very slippery until dry.
- Before first application of Iron Stone<sup>®</sup> Acrylic Seal remove all old coatings with any Diversey stripper

#### Coating

- Apply 1–2 uniform coats of Iron Stone® Acrylic Seal using a clean mop
- Allow 30–45 minutes drying time between coats. Temperature, humidity and ventilation may affect drying time.

#### **Top Coating**

• Use Diversey finish based on desired gloss and equipment

Technical data	Iron Stone® Acrylic Seal
Color/Form	Opaque white, liquid
рН	8.2
Scent	Solvent ammonia
Shelf Life	2 Years

Product	Pack size	Dilution	Product code
Iron Stone® Acrylic Seal	4 x 1 gal. / 3.78 L Containers	Ready-to-use	4006110
Iron Stone® Acrylic Seal	1 x 5 gal. / 18.9 L Envirobox <sup>TM/MC</sup>	Ready-to-use	5104837

## Safe handling

Please make sure your employees read and understand the product label and Safety Data Sheet before using this product. The label contains directions for use; and both the label and SDS contain hazard warnings, precautionary statements and first aid procedures. SDS are available online at www.diversey.com or by calling 888.352.2249. Improper use or dilution may result in damage to surfaces and may result in health and physical hazards that match those of the concentrate. Please refer to the Diversey HazMat Library, only available through Internet Explorer, http://naextranet.diversey.com/dot/, for up-to-date shipping information.