



### Quick Links

[Facilities Website](#)

[Safety Data Sheets \(SDS\)](#)

Some of these links lead to web-based resources that are not product-specific.

## Product Description

3M™ Melamine Floor Pads are uniquely formulated from high-strength melamine foam, bound with adhesive to dramatically improve their abrasive strength and durability. This open cell structure makes light work of ingrained dirt and unsightly scuff marks.

## Applications

Ideal for most bare stone and grouted surfaces such as ceramic, granite, marble, terrazzo, terracotta, and concrete.

Ideal for most uncoated textured resilient floors such as Luxury Vinyl Tile (LVT) and sheet vinyl.

## Features and Benefits

- Use wet with or without cleaning chemicals
- Eraser-like effect on stubborn black marks
- Cleans effectively with water alone
- Swing machines, rotary floor machines, low speed automatic scrubbers and fits all standard pad holders
- Available in a variety of sizes
- A one-sided pad which has a white polyester fleece backing for improved grip under the machine

## Packaging and Marking

Each carton shall be labeled to identify the contents by product name, size, quantity and manufacturer. Each pad shall be printed with the manufacturer's name.

## Standard Sizes

Circular discs are available in a variety of common sizes. Pads are nominally one inch thick.

## Pad Use and Cleaning

Dust mop entire floor prior to cleaning. Install appropriate sized 3M™ Melamine Floor Pad/s on your low speed (175 to 350 RPM) cleaning equipment, melamine side down. Fill the scrubber tank or mop bucket with water or properly diluted cleaning solution. Clean floor.

Pads may be rinsed with water to remove soil and debris as needed.

Do not use with high or low pH cleaners or cleaning products containing chlorine.

Durability highly depends on floor structure and method of use.

## Storage

Store indoors in original packaging and under normal facility conditions.

## Product Characteristics

3M™ Melamine Floor Pad		Test Method
Fiber Type	Melamine & white polyester fleece backing	N/A
O.D. Dimension	Designated Size ± 1/16 in.	CCD0004
Thickness	1 in. nominal	CCD0002
Aggressiveness	N/A	CCD0020

 **DANGER**

To reduce the risks associated with inhalation of or exposure to contaminants:

DO NOT use this product on any asbestos-containing material.

 **WARNING**

To reduce the risks associated with inhalation of or exposure to contaminants:

- Ensure this product is used in the recommended applications with the suggested equipment.
- Do not allow this product to be used by untrained operators.
- Always follow standard safety practices, including wearing appropriate protective apparel and eye protection while using this product.

## Health and Safety

 **CAUTION**

When handling any chemical products, read the manufacturers' container labels and the Safety Data Sheets (SDS) for important health, safety and environmental information. To obtain SDS sheets for 3M products go to [3M.com/SDS](https://www.3m.com/SDS), or by mail or in case of an emergency, call 1- 888-364-3577 or 1-651-737-6501.

When using any equipment, always follow the manufacturers' instructions for safe operation.

## Technical Information

The technical information, guidance, and other statements contained in this document or otherwise provided by 3M are based upon records, tests, or experience that 3M believes to be reliable, but the accuracy, completeness, and representative nature of such information is not guaranteed. Such information is intended for people with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. No license under any 3M or third party intellectual property rights is granted or implied with this information. If you have questions about this Product, contact the **Customer Service Department at 1-800-626-8578**.

## Product Selection and Use

Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application, including conducting a workplace hazard assessment and reviewing all applicable regulations and standards (e.g., OSHA, ANSI, etc.). Failure to properly evaluate, select, and use a 3M product and appropriate safety products, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property.

## Warranty, Limited Remedy, and Disclaimer

Unless a different warranty is specifically stated on the applicable 3M product packaging or product literature (in which case such warranty governs), 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. If a 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

## Limitation of Liability

Except for the limited remedy stated above, and except to the extent prohibited by law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.

### Commercial Solutions

3M Center, Building 220-12E-04  
St. Paul, MN 55144

1-800-626-8578  
[3M.com/Facility](https://www.3m.com/Facility)

© 3M 2021. All rights reserved.  
3M is the trademark of 3M.  
Used under license in Canada.  
All other trademarks are property of their respective owners.  
Revision A, April 2021 Please recycle.

**3M** Science.  
Applied to Life.™