



GC108CEZ SURGE PROTECTOR

Power, surge protection and USB charging solutions for home and office electronics

The CyberPower GC108CEZ surge protector and charger brings you power, protection, and versatility – all in one compact unit. The GC108CEZ is equipped with one standard, grounded AC power outlet with 500J of surge protection, two USB-A charging ports with 2.4 amps of charging power and two USB-C charging ports rated at 15 watts maximum. With its mix of an AC outlet, USB ports, and an eight-foot long power cord, the GC108CEZ is an ideal solution for desk tops, table tops and other areas of the home or office where access to power is needed.

Features of the GC108CEZ include one standard outlet, metal oxide varistor (MOV) technology, eight-foot power cord, two USB-A and two USB-C charging ports, and an impact-resistant casing. This surge suppressor comes with a One-Year Limited Warranty and a Connected Equipment Guarantee.



TYPICAL APPLICATIONS

- Mobile Devices
- Personal Electronics
- Cell Phones
- Personal Computers

FEATURES

- Surge suppression: 500 J
- Outlets: 1
- Outlet type: NEMA 5-15R
- Cord Length: 8 ft.
- Plug type: Low-profile
- USB-C charge ports: 2
- USB-C Output: 15W max
- USB-A charge ports: 2
- USB-A Output: 2.4A shared
- Volts: 125 V
- Warranty: 1-Year Limited
- Connected Equipment Guarantee: \$25,000

SPECIFICATIONS

| INPUT | |
|-----------------------|--------------|
| Cord Length | 8 ft (2.4 m) |
| Input Plug Type | NEMA 5-15P |
| Input Voltage | 125 VAC |
| Maximum Input Current | 15 A |
| Plug Style | Low-Profile |

| OUTPUT | |
|--------------------------|-------------------------|
| Outlet Type | 1 x NEMA 5-15R |
| Outlets – Total | 1 |
| USB Charge Port | Yes |
| USB Charge Port Amperage | 4 A (Shared) |
| USB Charge Port Quantity | 4 |
| USB Charge Port Type | 2 x Type A / 2 x Type C |
| USB Charge Port Voltage | 5 VDC |
| USB Charge Port Watts | 15 Watts |

GC108CEZ

SURGE PROTECTOR

SPECIFICATIONS CONT.

| SURGE PROTECTION & FILTERING | |
|--|------------------------|
| Clamping Voltage | 900V (H-N) |
| EMI/RFI Filtration | No |
| Maximum Surge Current | 15,000 A |
| Maximum Surge Current H-N | 15,000 A |
| Maximum Surge Voltage | 6,000 A |
| Response Time | <1 Nanosecond |
| Surge Suppression (Joules) | 500 J |
| PHYSICAL | |
| Color | White |
| Material of Construction | Plastic |
| PHYSICAL DIMENSIONS | |
| Physical Dimensions - Width/Height/Depth (cm) | 8.51 x 3.4 x 7.98 cm |
| Physical Dimensions - Width/Height/Depth (mm) | 85 x 34 x 80 mm |
| Physical Dimensions - Width/Height/Depth (in.) | 3.35 x 1.34 x 3.14 in. |
| Weight (kg) | 0.29 kg |
| Weight (lb) | 0.65 lbs. |

| SHIPPING DIMENSIONS | |
|---|--|
| Shipping Dimensions - Width/Height/Depth (cm) | 14.0 x 16.51 x 3.99 cm |
| Shipping Dimensions - Width/Height/Depth (mm) | 139.95 x 165.1 x 39.88 mm |
| Shipping Dimensions - Width/Height/Depth (in) | 5.51 x 6.5 x 1.57 in. |
| Weight (kg) | 0.37 kg |
| Weight (lb) | 0.82 lbs. |
| CERTIFICATIONS | |
| Environmental | RoHS Compliant |
| Safety | ETL US UL1363 UL1449 UL1310 FCC DOE VI CEC |
| WARRANTY | |
| CEG Amount | \$25,000 |
| Connected Equipment Guarantee | Lifetime |
| Product Warranty | One-Year Limited Warranty |