



SMP3

Overview

SMP3 power supply/charger converts a low voltage AC input into a 6VDC, 12VDC or 24VDC output. This unit has a wide range of applications for access control, security and CCTV system accessories that require additional power.

Specifications

Input:

- 16VAC to 28VAC.

Output:

- 6VDC, 12VDC or 24VDC selectable output.
- 2.5 amp continuous supply current.
- Filtered and electronically regulated output.
- Short circuit and thermal overload protection.

Battery Backup:

- Built-in charger for sealed lead acid or gel type batteries.
- Automatic switch over to stand-by battery when AC fails.
- Maximum charge current 0.3 amp.
- Battery short circuit protection (circuit breaker).

Visual Indicators:

- AC input and DC output LED indicators.

Electrical:

- Operating temperature: -20°C to 49°C ambient.
- BTU/Hr.:
 - 6VDC: 7.68 BTU/Hr.
 - 12VDC: 15.35 BTU/Hr.
 - 24VDC: 30.71 BTU/Hr.
- System AC input VA requirement:
 - 6VDC/12VDC: 55.2VA.
 - 24VDC: 115VA.

Features:

- Extremely compact design.
- Includes battery leads.
- Snap Track compatible (order Altronix model number ST3).

Mechanical:

- Board Dimensions (L x W x H approx.): 3.5" x 3" x 2" (88.9mm x 76.2mm x 50.8mm)
- Product weight (approx.): 0.25 lbs. (0.113 kg).
- Shipping weight (approx.): 0.35 lbs. (0.158 kg).

Board Dimensions (W x L x H approximate):

3" x 3.5" x 2" (76.2mm x 88.9mm x 50.8mm)

